

SAFETY DATA SHEET

Creation Date 01-Sep-2009

Revision Date 21-Feb-2024

Revision Number 7

1. Identification				
Product Name	2-Propanol			
Cat No. :	A416-1; A416-4; A416-4LC; A416-20; A416-200; A416-200LC; A416-500; A416FB-19; A416FB-50; A416FB-115; A416FB-200; A416P-4; A416RB-50; A416RB-115; A416RB-200; A416RS-28; A416RS-50; A416RS-115; A416RS-200; A416S-4; A416SK-4; A416SK4-001; A416SS-28; A416SS-50; A416SS-115; A416SS-200; XXA416ET4LI; XXA416LS200LI; NC1348124; XXA416250GAL; NC1535916; A416RS-200ASME; NC1568699; A416RS1350ASME; NC1561773; NC1664140; XXA416ET200LI; NC3347687; NC1812445; XXA416RC275GAL; NC1871382; A416ETRS1350ASM; A416RS1250; NC2009250; NC2745530; A416SS-19; NC1949489; NC2592436; A416RS19; NC3794760			
CAS No Synonyms	67-63-0 2-Propanol; IPA; Isopropyl alcohol; Propan-2-ol; Isopropanol			
Recommended Use Uses advised against	Laboratory chemicals. Food, drug, pesticide or biocidal product use.			

Details of the supplier of the safety data sheet

<u>Company</u>

Fisher Scientific Company One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system	(CNS).
Specific target organ toxicity - (repeated exposure)	Category 2

Target Organs - Kidney, Liver.

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure



Precautionary Statements Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition/information on Ingredients

Component		CAS No	Weight %		
Isopropyl alcohol		67-63-0	>95		
	4. First-aid measures				
Eye Contact	Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Ge medical attention.				
Skin Contact	Wash off imr symptoms or	nediately with plenty of water for at least	15 minutes. Get medical attention if		
Inhalation	Remove to fr	esh air. Get medical attention. If not bre	athing, give artificial respiration.		
Ingestion	Do NOT indu	ice vomiting. Get medical attention.			
Most important symptoms and effects	Difficulty in breathing. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea				
Notes to Physician	and vomiting Treat symptomatically				
	5. Fi	re-fighting measures			
Suitable Extinguishing Media CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.					
Unsuitable Extinguishing Media	Water may b	e ineffective			
Flash Point	12 °C / 53	6 °F			
Method -	Abel Closed Cup (BS 2000 Part 170, IP 170, AS/NZS 2106)				
Autoignition Temperature	425 °C / 797 °F				
Explosion Limits Upper Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	12 vol % 2 vol % t No informatio No informatio				

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). peroxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

<u>NFPA</u>	Health 2	Flammability 3	Instability 0	Physical hazards N/A
		6. Accidental rel	ease measures	
	I Precautions	precautionary measures ag		contact with skin, eyes or clothing.
Environ	mental Precautions	Should not be released into	the environment. See Section	12 for additional Ecological

Information.

Methods for Containment and Clean Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Keep in suitable, closed containers for disposal.

	7. Handling and Storage				
Handling	Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.				
Storage.	Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Acids. Halogens. Acid anhydrides.				

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1225	IDLH: 2000 ppm REL = 400 ppm (TWA) REL = 980 mg/m ³ (TWA) STEL: 500 ppm	TWA: 200 ppm STEL: 400 ppm
		mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³	STEL: 1225 mg/m ³	

<u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Ensure that eyewash stations and safety showers are close to the workstation location. I explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.	
Personal Protective Equipment		
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.	
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.	
Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.	
Recommended Filter type:	Organic gases and vapours filter. Type A. Brown. conforming to EN14387.	
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.	
	9. Physical and chemical properties	

Physical State	Liquid	
Appearance	Colorless	
Odor	Alcohol-like	
Odor Threshold	No information available	
рН	7	1% aq. sol
Melting Point/Range	-89.5 °C / -129.1 °F	
Softening Point	No data available	
Boiling Point/Range	81 - 83 °C / 177.8 - 181.4 °F	@ 760 mmHg
Flash Point	12 °C / 53.6 °F	Method - Abel Closed Cup (BS 2000 Part 170, IP
		170, AS/NZS 2106)
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 2 Vol%	
	Upper 12 Vol%	
Autoignition Temperature	425 °C / 797 °F	ASTM E-659
Decomposition Temperature	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/wat		
Component	log Pow	
Isopropyl alcohol	0.05	
Vapor Pressure	43 mmHg @ 20 °C	
Density / Specific Gravity	0.785	ASTM D-4052
Bulk Density	Not applicable 2.1 @ 20 °C / 68 °F	Liquid
Vapor Density	2.1 @ 20 C 7 68 F 2.27 mPa.s at 20 °C	(Air = 1.0)
Viscosity Particle characteristics	Not applicable (liquid)	
	Not applicable (liquid)	
Molecular Formula	C3 H8 O	
Molecular Weight	60.1	
VOC Content(%)	100% (Organic Carbon (by mass) = 5	59.9 %) (EC/1999/13)
Explosive Properties	Not explosive explosive air/vapour m	ixtures possible Vapors may form explosive mixtures
	with air	
Evaporation Rate	1.7 - ASTM D 3539 (Butyl acetate =	1.0)
Thermal conductivity	0.137 W/m °C at 20 °C / 68 °F	
Refractive index	1.377 at 20 °C / 68 °F (ASTM D-1218	3)
Surface tension	22.7 mN/m at 20 °C / 68 °F	
Coefficient of expansion	0.0009 / °C	
Specific heat capacity	3 kJ/kg °C at 20 °C / 68 °F	
Dielectric constant	18.6 at 20 °C / 68 °F	
Heat of vapourisation	665 J/g	

10. Stability and reactivity				
Reactive Hazard	None known, based on information available			
Stability	Stable under normal conditions.			
Conditions to Avoid	Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.			
Incompatible Materials	Strong oxidizing agents, Acids, Halogens, Acid anhydrides			
Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), peroxides				
Hazardous Polymerization	Hazardous polymerization does not occur.			

Hazardous Reaction	ns	None under normal processing.				
		11. Toxico	ological info	ormation		
Information on expe	ected route of ex	posure				
Inhalation			May be harmful if inhaled. May cause drowsiness and dizziness. May cause irritation of			
Ingestion		May cause central	respiratory tract. May cause central nervous system effects. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.			
Eyes		Irritating to eyes.				
Skin		Irritating to skin. M	lay be harmful in c	ontact with skin.		
Acute Toxicity						
Product Information Component Information						
Componer		LD50 Oral		LD50 Dermal		nhalation
Isopropyl alco	phol	5045 mg/kg (Rat) 3600 mg/kg (Mouse		800 mg/kg (Rat)	72.6 mg/	L(Rat)4 h
Toxicologically Syn	ergistic	No information ava			I	
Products						
Delayed and immed	liate effects as w	ell as chronic effe	ects from short an	d long-term expo	osure	
Irritation		Irritating to eyes a	nd skin			
Sensitization		No information ava	ailable			
Carcinogenicity		The table below in	dicates whether ea	ach agency has list	ted any ingredient a	as a carcinogen.
Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Isopropyl alcohol	67-63-0	Not listed	Not listed	Not listed	Not listed	Not listed
Mutagenic Effects		No information ava	allable			
Reproductive Effect	ts	No information ava	ailable.			
Developmental Effe	ects	No information ava	ailable.			
Teratogenicity		No information ava	ailable.			
• •	STOT - single exposureRespiratory system Central nervous system (CNS)STOT - repeated exposureKidney Liver					
Aspiration hazard	piration hazard No information available					
Symptoms / effects delayed	s,both acute and	d May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting				
Endocrine Disrupto	ptor Information No information available					
Other Adverse Effe	Other Adverse Effects The toxicological properties have not been fully investigated.					
12. Ecological information						

Ecotoxicity . Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	EC50: > 1000 mg/L, 72h	LC50: = 9640 mg/L, 96h	= 35390 mg/L EC50	13299 mg/L EC50 = 48 h
	(Desmodesmus	flow-through (Pimephales	Photobacterium	9714 mg/L EC50 = 24 h
	subspicatus)	promelas)	phosphoreum 5 min	_
	EC50: > 1000 mg/L, 96h	LC50: > 1400000 µg/L, 96h		

	(Desmodesmus	(Lepomis macrochirus)		
	subspicatus)	LC50: = 11130 mg/L, 96h		
	ousoproutuo)	static (Pimephales		
		LC50: = 10000000 µg/L, 96	h	
		(Daphnia)		
Persistence and Degrada	bility Dersisten	l ce is unlikely based on infori	mation available	
reisistence and Degrada				
Bioaccumulation/Accum	No inform	ation available.		
Mobility	Will likely	be mobile in the environmer	nt due to its volatility.	
	0		la v Dava	
	Component sopropyl alcohol		log Pow 0.05	
	оргоругаісопог		0.05	
	13.	Disposal conside	rations	
Waste Disposal Methods		waste generators must dete		chemical is classified as a
Waste Disposal methods		s waste. Chemical waste ge		
		azardous waste regulations		
	national n			
	14.	Transport inforn	nation	
DOT		•		
UN-No	UN1219			
Proper Shipping Nam	ie Isopropan	ol		
Hazard Class	3			
Packing Group	II.			
TDG				
UN-No	UN1219			
Proper Shipping Nam	ISOPROF	PANOL		
Hazard Class	3			
Packing Group	II			
IATA				
UN-No	UN1219			
Proper Shipping Nam	ne Isopropan	ol		
Hazard Class	3			
Packing Group	II			
IMDG/IMO				
UN-No	UN1219			
Proper Shipping Nam		ol (Isopropyl alcohol)		
Hazard Class	3			
Packing Group				

15. Regulatory Information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Isopropyl alcohol	67-63-0	Х	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710) X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Not applicable Substances & Mixtures, Under TSCA Section 6(h) (PBT)

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Isopropyl alcohol	67-63-0	Х	-	200-661-7	Х	Х	Х	Х	Х	KE-29363

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting threasholds
Isopropyl alcohol	67-63-0	>95	1.0 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)	Not applicable
Clean Air Act	Not applicable
OSHA - Occupational Safety and Health Administration	Not applicable

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isopropyl alcohol	Х	Х	Х	-	Х

U.S. Department of Transportation

Reportable Quantity (RQ):NDOT Marine PollutantNDOT Severe Marine PollutantN

This product doos not contain any DHS chamicals

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Isopropyl alcohol	67-63-0	-	Use restricted. See entry 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Isopropyl alcohol	67-63-0	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Isopropyl alcohol	67-63-0	Not applicable	Not applicable	Not applicable	Annex I - Y42

16. Other Information

Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com

Creation Date	01-Sep-2009
Revision Date	21-Feb-2024
Print Date	21-Feb-2024
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

Prepared By

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS