

SAFETY DATA SHEET

Creation Date 09-Nov-2010 Revision Date 24-Dec-2021 Revision Number 5

1. Identification

Product Name sec-Butylamine

Cat No.: AC107810000; AC107810010; AC107810025; AC107810050;

AC107810250; AC107811000; AC107815000

CAS No 13952-84-6 Synonyms 2-Aminobutane

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company Acros Organics
One Reagent Lane One Reagent Lane
Fair Lawn, NJ 07410 Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Acute oral toxicity

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Category 3

Category 1

Category 3

Target Organs - Respiratory system.

Label Elements

Signal Word

Danger

Revision Date 24-Dec-2021 sec-Butylamine

Hazard Statements

Highly flammable liquid and vapor Causes severe skin burns and eye damage May cause respiratory irritation Toxic if swallowed Harmful if inhaled



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Ingestion

Rinse mouth

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life

3. Composition/Information on Ingredients

Component	CAS No	Weight %
sec-Butylamine	13952-84-6	>95

4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim

ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh

air. Immediate medical attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Causes burns by all exposure routes. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray. Carbon dioxide (CO₂). Dry chemical. Water mist may be used to cool closed

containers. Chemical foam. Water mist may be used to cool closed containers. CO₂, dry

chemical, dry sand, alcohol-resistant foam.

Unsuitable Extinguishing Media No information available

Flash Point -19 °C / -2.2 °F

Method - No information available

Autoignition Temperature 355 °C / 671 °F

Explosion Limits

Upper 9.00% **Lower** 1.80%

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health Flammability Instability Physical hazards

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Environmental Precautions

Methods for Containment and Clean Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. **Up**Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Keep away from heat, sparks and flame. Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Store under an inert atmosphere. Corrosives area. Incompatible Materials. Acids. Strong oxidizing agents. sodium hypochlorite. Acid anhydrides. Acid chlorides. Metals. Carbon dioxide (CO2).

8. Exposure controls / personal protection

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use spark-proof tools and explosion-proof equipment. Use explosion-proof electrical/ventilating/lighting equipment.

Personal Protective Equipment

Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Appearance Odor Liquid
Clear
Ammonia-like
No information available

Odor Threshold

pH 13 100 g/L aq.sol

Revision Date 24-Dec-2021 sec-Butylamine

Melting Point/Range -104 °C / -155.2 °F

63 °C / 145.4 °F @ 760 mmHa **Boiling Point/Range**

-19 °C / -2.2 °F **Flash Point Evaporation Rate** No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

9.00% Upper Lower 1.80%

Vapor Pressure 180 hPa @ 20 °C **Vapor Density** 2.52 **Specific Gravity** 0.720

Solubility miscible

Partition coefficient; n-octanol/water No data available **Autoignition Temperature** 355 °C / 671 °F **Decomposition Temperature** No information available **Viscosity** 0.5 mPa.s at 20 °C

Molecular Formula C4 H11 N **Molecular Weight** 73.13

10. Stability and reactivity

None known, based on information available Reactive Hazard

Air sensitive. Stability

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition. Exposure to air.

Incompatible products.

Acids, Strong oxidizing agents, sodium hypochlorite, Acid anhydrides, Acid chlorides, **Incompatible Materials**

Metals, Carbon dioxide (CO2)

Hazardous Decomposition Products Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
sec-Butylamine	LD50 = 152 mg/kg (Rat)	LD50 = 2500 mg/kg (Rabbit)	Not listed

No information available **Toxicologically Synergistic**

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
sec-Butylamine	13952-84-6	Not listed				

Not mutagenic in AMES Test **Mutagenic Effects**

Reproductive Effects No information available.

•

Developmental EffectsNo information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed

tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and

danger of perforation

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms.

L	Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ī	sec-Butylamine	EC50: 0.54 mg/L/72h	LC50: 46-68 mg/L/96h	Not listed	EC50: 37.9 mg/L/48h
1			(Leuciscus idus)		

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
sec-Butylamine	0.74

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

<u>UN-No</u> UN2734

Proper Shipping Name AMINES, LIQUID, CORROSIVE, FLAMMABLE, N.O.S.

Technical Name sec-Butylamine

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group 1

TDG

UN2734

Proper Shipping Name AMINES, LIQUID, CORROSIVE, FLAMMABLE, N.O.S.

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group 1

IATA

UN2734

Proper Shipping Name AMINES, LIQUID, CORROSIVE, FLAMMABLE, N.O.S.

Hazard Class

Subsidiary Hazard Class 3
Packing Group

IMDG/IMO

UN-No UN2734

Proper Shipping Name AMINES, LIQUID, CORROSIVE, FLAMMABLE, N.O.S.

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group 1

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
sec-Butylamine	13952-84-6	Χ	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
sec-Butylamine	13952-84-6	Χ	-	237-732-7	Х	Χ	Х	Х	Х	KE-25291

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous CWA - Reportate Substances Quantities		CWA - Toxic Pollutants	CWA - Priority Pollutants	
sec-Butylamine	X	-	-	-	

Clean Air Act Not applicable

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
sec-Butylamine	1000 lb	-

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know

Regulations

	Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ī	sec-Butylamine	X	X	X	=	-

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Component		REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
sec-Butylamine	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)			
sec-Butylamine	13952-84-6	Not applicable	Not applicable	Not applicable	Not applicable			
Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities	, ,	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)			
sec-Butylamine	13952-84-6	for Major Accident Notification Not applicable	for Safety Report Requirements Not applicable	Not applicable	Not applicable			

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 09-Nov-2010

 Revision Date
 24-Dec-2021

 Print Date
 24-Dec-2021

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS