

# **SAFETY DATA SHEET**

Creation Date 01-Sep-2009 Revision Date 24-Dec-2021 Revision Number 5

1. Identification

Product Name Isopropanol

Cat No.: AC184130000; AC184130010; AC184130025; AC184130051;

AC184130100; AC184130250

**CAS No** 67-63-0

Synonyms 2-Propanol; IPA; Isopropyl alcohol; Propan-2-ol; Isopropanol

Recommended Use Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

### Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

# 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2
Serious Eye Damage/Eye Irritation Category 2

Specific target organ toxicity (single exposure)

Category 2

Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure) Category 2

Target Organs - Kidney, Liver.

#### Label Elements

# Signal Word

Danger

#### **Hazard Statements**

Highly flammable liquid and vapor
Causes serious eye irritation
May cause respiratory irritation
May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure



### **Precautionary Statements**

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

# Response

Get medical attention/advice if you feel unwell

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

#### Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

#### Disposal

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

None identified

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Isopropyl alcohol	67-63-0	>95

# 4. First-aid measures

**Eve Contact** 

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Revision Date 24-Dec-2021 Isopropanol

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

symptoms occur.

Inhalation Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.

Do NOT induce vomiting. Get medical attention. Ingestion

Most important symptoms and

effects

Difficulty in breathing. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea

and vomiting

Notes to Physician Treat symptomatically

# Fire-fighting measures

**Suitable Extinguishing Media** CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

**Unsuitable Extinguishing Media** Water may be ineffective

12 °C / 53.6 °F **Flash Point** 

Method -Abel Closed Cup (BS 2000 Part 170, IP 170, AS/NZS 2106)

**Autoignition Temperature** 425 °C / 797 °F

**Explosion Limits** 

12 vol % Upper Lower 2 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>), peroxides.

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health Flammability Instability Physical hazards 2 3 N/A

## Accidental release measures

Use personal protective equipment as required. Remove all sources of ignition. Take **Personal Precautions** 

precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Should not be released into the environment. See Section 12 for additional Ecological

Information.

**Environmental Precautions** 

αU

Methods for Containment and Clean Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Keep in suitable, closed containers for disposal.

# 7. Handling and storage

**Handling** Wear personal protective equipment/face protection. Keep away from open flames, hot

surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage. Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in

a dry and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Acids.

Halogens. Acid anhydrides.

# 8. Exposure controls / personal protection

#### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm	TWA: 200 ppm
1	STEL: 400 ppm	(Vacated) TWA: 980 mg/m <sup>3</sup>	TWA: 400 ppm	STEL: 400 ppm
		(Vacated) STEL: 500 ppm	TWA: 980 mg/m <sup>3</sup>	
		(Vacated) STEL: 1225	STEL: 500 ppm	
		mg/m³	STEL: 1225 mg/m <sup>3</sup>	
		TWA: 400 ppm		
		TWA: 980 mg/m <sup>3</sup>		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure that eyewash stations and safety showers are close to the workstation location. Use

explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation,

especially in confined areas.

Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

**Respiratory Protection**When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical State Liquid
Appearance Colorless
Odor Alcohol-like

Odor Threshold No information available

1 7 1% ag. sol

Melting Point/Range -89.5 °C / -129.1 °F

Boiling Point/Range 81 - 83 °C / 177.8 - 181.4 °F @ 760 mmHg

Flash Point 12 °C / 53.6 °F

Method - Abel Closed Cup (BS 2000 Part 170, IP 170, AS/NZS 2106)

Evaporation Rate

Flammability (solid.gas)

Not applicable

Flammability or explosive limits

Upper 12 vol %

Lower 2 vol %

Specific Gravity 0.785

Solubility

Partition coefficient; n-octanol/water

Autoignition Temperature

Decomposition Temperature

Miscible with water

No data available

425 °C / 797 °F

No information available

Viscosity

No information available 2.27 mPa.s at 20 °C

Molecular Formula C3 H8 O
Molecular Weight 60.1

**VOC Content(%)** 100% (Organic Carbon (by mass) = 59.9 %) (EC/1999/13)

Refractive index 1.377 at 20 °C / 68 °F (ASTM D-1218)

Surface tension 22.7 mN/m at  $20 \,^{\circ}\text{C} / 68 \,^{\circ}\text{F}$ 

Coefficient of expansion 0.0009 / °C

Dielectric constant 18.6 at 20 °C / 68 °F

Heat of vapourisation 665 J/g

**Specific heat capacity** 3 kJ/kg  $^{\circ}$ C at 20  $^{\circ}$ C / 68  $^{\circ}$ F **Thermal conductivity** 0.137 W/m  $^{\circ}$ C at 20  $^{\circ}$ C / 68  $^{\circ}$ F

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of

ignition.

Incompatible Materials Strong oxidizing agents, Acids, Halogens, Acid anhydrides

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), peroxides

**Hazardous Polymerization** Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

## 11. Toxicological information

# **Acute Toxicity**

#### **Product Information**

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5045 mg/kg (Rat)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
	3600 mg/kg (Mouse)		

Toxicologically Synergistic No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

 Irritation
 Irritating to eyes and skin

 Sensitization
 No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Isopropyl alcohol	67-63-0	Not listed				

Mutagenic Effects No information available

**Reproductive Effects**No information available.

Revision Date 24-Dec-2021 Isopropanol

**Developmental Effects** No information available.

**Teratogenicity** No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

Kidney Liver STOT - repeated exposure

No information available **Aspiration hazard** 

delayed

Symptoms / effects, both acute and May cause central nervous system depression: Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting

No information available **Endocrine Disruptor Information** 

Other Adverse Effects The toxicological properties have not been fully investigated.

# 12. Ecological information

#### **Ecotoxicity**

. Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	EC50: > 1000 mg/L, 96h	LC50: = 9640 mg/L, 96h	= 35390 mg/L EC50	13299 mg/L EC50 = 48 h
	(Desmodesmus	flow-through (Pimephales	Photobacterium	9714 mg/L EC50 = 24 h
	subspicatus)	promelas)	phosphoreum 5 min	
	EC50: > 1000 mg/L, 72h	LC50: > 1400000 µg/L, 96h		
	(Desmodesmus	(Lepomis macrochirus)		
	subspicatus)	LC50: = 11130 mg/L, 96h		
		static (Pimephales		
		promelas)		
		LC50: = 10000000 µg/L, 96h		
		(Daphnia)		

Persistence and Degradability Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

Will likely be mobile in the environment due to its volatility. **Mobility** 

Component	log Pow
Isopropyl alcohol	0.05

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

# 14. Transport information

DOT

UN1219 **UN-No Proper Shipping Name** Isopropanol

**Hazard Class** 3 **Packing Group** Ш

TDG

**UN-No** UN1219

**Proper Shipping Name ISOPROPANOL** 

**Hazard Class Packing Group** Ш

IATA

UN1219 **UN-No** 

Proper Shipping Name Isopropanol

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1219

Proper Shipping Name Isopropanol (Isopropyl alcohol)

Hazard Class 3
Packing Group ||

# 15. Regulatory information

## **United States of America Inventory**

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Isopropyl alcohol	67-63-0	X	ACTIVE	-

#### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Isopropyl alcohol	67-63-0	Х	-	200-661-7	X	X	X	X	Х	KE-29363

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

## U.S. Federal Regulations

### **SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	>95	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** - Occupational Safety and

Health Administration

Not applicable

CERCLA Not applicable

**California Proposition 65** This product does not contain any Proposition 65 chemicals.

### U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isopropyl alcohol	X	X	X	-	X

## **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

**Security** 

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

#### Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV -	REACH (1907/2006) - Annex XVII -	REACH Regulation (EC
	Substances Subject to	Restrictions on Certain Dangerous	1907/2006) article 59 - Candidate
	Authorization	Substances	List of Substances of Very High
			Concern (SVHC)
Isopropyl alcohol	-	Use restricted. See item 75.	-
		(see link for restriction details)	

https://echa.europa.eu/substances-restricted-under-reach

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Isopropyl alcohol	67-63-0	Listed	Not applicable	Not applicable	Not applicable
Component	CAS No	Seveso III Directive   Seveso III Directive   Rotterdam		Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)

Component	CAS No	Seveso III Directive	Seveso III Directive	Rotterdam	Basel Convention
		(2012/18/EC) -	(2012/18/EC) -	Convention (PIC)	(Hazardous Waste)
	Qualifying Quantities Qualifying Quantities				
		for Major Accident	for Safety Report		
		Notification	Requirements		
Isopropyl alcohol	67-63-0	Not applicable	Not applicable	Not applicable	Annex I - Y42

## 16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 01-Sep-2009

 Revision Date
 24-Dec-2021

 Print Date
 24-Dec-2021

**Revision Summary**This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# **End of SDS**