

SAFETY DATA SHEET

Creation Date 19-Nov-2009

Revision Date 14-Mar-2026

Revision Number 8

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard 2024 (29 CFR 1910.1200)

1. Identification

Product Name Petroleum ether, boiling range 60-95°C

Cat No. : AC235070000; AC235070010; AC235070025

CAS No 64742-49-0
Synonyms Ligroine

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous according to [US] OSHA (29 CFR 1910.1200, 2024)

Flammable liquids	Category 2
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Central nervous system (CNS), Peripheral Nervous System (PNS).	
Aspiration Toxicity	Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness
Suspected of damaging fertility
May cause damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Keep cool
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground and bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Wear protective gloves/protective clothing/eye protection/face protection
Take action to prevent static discharges
Use non-sparking tools

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Skin

Take off contaminated clothing and wash before reuse
If skin irritation occurs: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam to extinguish

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available

WARNING. Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/information on Ingredients

Component	CAS No	Weight %
Naphtha (petroleum), hydrotreated light	64742-49-0	>95
Hexane	110-54-3	<5
Cyclohexane	110-82-7	<1.5

4. First-aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Most important symptoms and effects	Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire
Flash Point	-20 °C / -4 °F
Method -	No information available
Autoignition Temperature	258 °C / 496.4 °F
Explosion Limits	
Upper	8.00%
Lower	0.60%
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
3

Flammability
3

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment and Clean Up	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and Storage

Handling	Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
Storage.	Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Hexane	TWA: 50 ppm Skin	(Vacated) TWA: 50 ppm (Vacated) TWA: 180 mg/m ³ TWA: 500 ppm TWA: 1800 mg/m ³	IDLH: 1100 ppm REL = 50 ppm (TWA) REL = 180 mg/m ³ (TWA)	TWA: 50 ppm
Cyclohexane	TWA: 100 ppm	(Vacated) TWA: 300 ppm (Vacated) TWA: 1050 mg/m ³ TWA: 300 ppm TWA: 1050 mg/m ³	IDLH: 1300 ppm REL = 300 ppm (TWA) REL = 1050 mg/m ³ (TWA)	TWA: 100 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.
-----------------------------	---

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: low boiling organic solvent. Type AX. Brown. conforming to EN371.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance

Physical State

Liquid

Color

Colorless

Odor

Petroleum distillates

Odor Threshold

No information available

Property

Values

Remarks

• Method

Melting Point/Range

-40 °C / -40 °F

Softening Point

No data available

Boiling Point/Range

60 - 100 °C / 140 - 212 °F

@ 760 mmHg

Flash Point

-20 °C / -4 °F

Method - No information available

Flammability (liquid)

Highly flammable

On basis of test data

Flammability (solid,gas)

Not applicable

Liquid

Explosion Limits

Lower 1.1 vol%

Upper 7.4 vol%

Autoignition Temperature

258 °C / 496.4 °F

Decomposition Temperature

No data available

pH

No information available

Viscosity

0.57 cSt @ 25°C

Water Solubility

Insoluble

Solubility in other solvents

No information available

Partition Coefficient (n-octanol/water)

Component

log Pow

Hexane

4.11

Cyclohexane

3.44

Vapor Pressure

105 mmHg @ 20°C

Density / Specific Gravity

0.700

Bulk Density

Not applicable

Liquid

Vapor Density

No data available

(Air = 1.0)

Particle characteristics

Not applicable (liquid)

Other Information

Explosive Properties

Vapors may form explosive mixtures with air

10. Stability and reactivity

Reactive Hazard

None known, based on information available

Stability

Stable under normal conditions.

Conditions to Avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO₂)

Hazardous Polymerization

Hazardous polymerization does not occur.

Hazardous Reactions

None under normal processing.

11. Toxicological information

Information on expected route of exposure

Inhalation	Avoid breathing vapors or mists.
Ingestion	May be harmful if swallowed. Potential for aspiration if swallowed.
Eyes	Avoid contact with eyes. May cause irritation.
Skin	Avoid contact with skin. May cause irritation. Prolonged skin contact may defat the skin and produce dermatitis.

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Naphtha (petroleum), hydrotreated light	LD50 > 5000 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit)	LC50 = 73680 ppm (Rat) 4 h
Hexane	LD50 = 25 g/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 = 48000 ppm (Rat) 4 h
Cyclohexane	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	LC50 > 32880 mg/m ³ (Rat) 4 h

Toxicologically Synergistic Products No information available

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;
Respiratory Based on available data, the classification criteria are not met
Skin Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen. Petroleum products are known to cause cancer because of carcinogenic components (e.g. benzene). These carcinogenic components may be removed during the refinement process. The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen. This note applies only to certain complex oil derived substances in Annex I

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Naphtha (petroleum), hydrotreated light	64742-49-0	Not listed	Not listed	Not listed	Not listed	Not listed
Hexane	110-54-3	Not listed	Not listed	Not listed	Not listed	Not listed
Cyclohexane	110-82-7	Not listed	Not listed	Not listed	Not listed	Not listed

(g) reproductive toxicity; Category 2

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Other Adverse Effects The toxicological properties have not been fully investigated.

Endocrine Disrupting Properties This product does not contain any known or suspected endocrine disruptors.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Naphtha (petroleum), hydrotreated light	Not listed	LC50: = 8.41 mg/L, 96h semi-static, closed (Oncorhynchus mykiss)	Not listed	Not listed
Hexane	Not listed	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	Not listed	EC50: 3.87 mg/L/48h
Cyclohexane	EC50 >500 mg/L/72h	LC50: 48.87 - 68.76 mg/L, 96h static (Poecilia reticulata) LC50: 24.99 - 44.69 mg/L, 96h static (Lepomis macrochirus) LC50: 23.03 - 42.07 mg/L, 96h static (Pimephales promelas) LC50: 3.96 - 5.18 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	EC50 = 0.9 mg/L/48h

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Hexane	4.11
Cyclohexane	3.44

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Cyclohexane - 110-82-7	U056	-

14. Transport information

DOT

UN-No UN3295
Proper Shipping Name Hydrocarbons, liquid, n.o.s.

Technical Shipping Name	Petroleum ether, boiling range 60-95°C
Hazard Class	3
Packing Group	II
TDG	
UN-No	UN3295
Proper Shipping Name	Hydrocarbons, liquid, n.o.s.
Technical Shipping Name	Petroleum ether, boiling range 60-95°C
Hazard Class	3
Packing Group	II
IATA	
UN-No	UN3295
Proper Shipping Name	Hydrocarbons, liquid, n.o.s.
Technical Shipping Name	Petroleum ether, boiling range 60-95°C
Hazard Class	3
Packing Group	II
IMDG/IMO	
UN-No	UN3295
Proper Shipping Name	Hydrocarbons, liquid, n.o.s.
Technical Shipping Name	Petroleum ether, boiling range 60-95°C
Hazard Class	3
Packing Group	II

15. Regulatory Information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Naphtha (petroleum), hydrotreated light	64742-49-0	X	ACTIVE	-
Hexane	110-54-3	X	ACTIVE	-
Cyclohexane	110-82-7	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Naphtha (petroleum), hydrotreated light	64742-49-0	X	-	265-151-9	X	-		X	X	KE-25623
Hexane	110-54-3	X	-	203-777-6	X	X	X	X	X	KE-18626
Cyclohexane	110-82-7	X	-	203-806-2	X	X	X	X	X	KE-18562

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold	SARA 313 - Reporting
-----------	--------	----------	----------------------	----------------------

			Values %	thresholds
Hexane	110-54-3	<5	1.0 %	-
Cyclohexane	110-82-7	<1.5	1.0 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Cyclohexane	X	1000 lb	-	-

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Hexane	X		-

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Hexane	5000 lb	-	5000 lb 2270 kg
Cyclohexane	1000 lb	-	1000 lb 454 kg

California Proposition 65 This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Hexane	110-54-3	Male Reproductive	-	Developmental

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Hexane	X	X	X	X	X
Cyclohexane	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
-----------	--------	---------------------	---------------------	----------------------

		Annex XIV - Substances Subject to Authorization	Annex XVII - Restrictions on Certain Dangerous Substances	1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Naphtha (petroleum), hydrotreated light	64742-49-0	-	Use restricted. See entry 28. (see link for restriction details) Use restricted. See entry 29. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Hexane	110-54-3	-	Use restricted. See entry 75. (see link for restriction details)	SVHC candidate list - EC 203-777-6 - Specific target organ toxicity after repeated exposure Article 57(f) - human health
Cyclohexane	110-82-7	-	Use restricted. See entry 57. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

<https://echa.europa.eu/candidate-list-table>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Naphtha (petroleum), hydrotreated light	64742-49-0	Listed	Not applicable	Not applicable	Not applicable
Hexane	110-54-3	Listed	Not applicable	Not applicable	Not applicable
Cyclohexane	110-82-7	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Naphtha (petroleum), hydrotreated light	64742-49-0	2500 tonne	25000 tonne	Not applicable	Not applicable
Hexane	110-54-3	Not applicable	Not applicable	Not applicable	Annex I - Y42
Cyclohexane	110-82-7	Not applicable	Not applicable	Not applicable	Not applicable

16. Other Information

Prepared By	Product stewardship (Regulatory Affairs) Thermo Fisher Scientific email - begel.sdsdesk@thermofisher.com
Creation Date	19-Nov-2009
Revision Date	14-Mar-2026
Print Date	14-Mar-2026
Revision Summary	Updated to the U.S. Department of Labor's Occupational Safety and Health Administration (OSHA) which published its Final Rule in the Federal Register revising the Hazard Communication Standard (HCS/HazCom), 29 CFR 1910.1200 (2024) (HCS §1910.1200, 2024), May 20, 2024, effective July 19, 2024.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS