

# SAFETY DATA SHEET

Creation Date 19-Nov-2009

Revision Date 14-Mar-2026

Revision Number 8

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard 2024 (29 CFR 1910.1200)

## 1. Identification

**Product Name** Petroleum ether, boiling range 60-95°C

**Cat No. :** AC292510000; AC292510010; AC292510025; AC292510100

**CAS No** 64742-49-0  
**Synonyms** Ligroine

**Recommended Use** Laboratory chemicals.  
**Uses advised against** Food, drug, pesticide or biocidal product use.

### Details of the supplier of the safety data sheet

#### Company

Fisher Scientific Company  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

Acros Organics  
One Reagent Lane  
Fair Lawn, NJ 07410

#### **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## 2. Hazard(s) identification

### Classification

This chemical is considered hazardous according to [US] OSHA (29 CFR 1910.1200, 2024)

Flammable liquids	Category 2
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Central nervous system (CNS), Peripheral Nervous System (PNS).	
Aspiration Toxicity	Category 1

### Label Elements

**Signal Word**

Danger

**Hazard Statements**

Highly flammable liquid and vapor  
May be fatal if swallowed and enters airways  
Causes skin irritation  
Causes serious eye irritation  
May cause drowsiness or dizziness  
Suspected of damaging fertility  
May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Keep cool  
Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wash face, hands and any exposed skin thoroughly after handling  
Wear eye/face protection  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container tightly closed  
Ground and bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting equipment  
Wear protective gloves/protective clothing/eye protection/face protection  
Take action to prevent static discharges  
Use non-sparking tools

**Response**

IF exposed or concerned: Get medical attention/advice

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing

**Skin**

Take off contaminated clothing and wash before reuse

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

**Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

**Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish

**Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Toxic to aquatic life with long lasting effects

**Hazards classified under paragraph (d)(1)(ii) of 1910.1200**

No information available  
 WARNING. Reproductive Harm - <https://www.p65warnings.ca.gov/>.

### 3. Composition/information on Ingredients

Component	CAS No	Weight %
Naphtha (petroleum), hydrotreated light	64742-49-0	>95
Hexane	110-54-3	<5
Cyclohexane	110-82-7	<1.5

### 4. First-aid measures

<b>General Advice</b>	If symptoms persist, call a physician.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Most important symptoms and effects</b>	Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
<b>Notes to Physician</b>	Treat symptomatically

### 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Water spray, carbon dioxide (CO <sub>2</sub> ), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
<b>Unsuitable Extinguishing Media</b>	Do not use a solid water stream as it may scatter and spread fire
<b>Flash Point</b>	-20 °C / -4 °F
<b>Method -</b>	No information available
<b>Autoignition Temperature</b>	258 °C / 496.4 °F
<b>Explosion Limits</b>	
<b>Upper</b>	8.00%
<b>Lower</b>	0.60%
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

#### Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

#### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**NFPA**

<b>Health</b> 3	<b>Flammability</b> 3	<b>Instability</b> 0	<b>Physical hazards</b> N/A
--------------------	--------------------------	-------------------------	--------------------------------

**6. Accidental release measures**

- Personal Precautions** Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
- Environmental Precautions** Do not flush into surface water or sanitary sewer system.
- Methods for Containment and Clean Up** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

**7. Handling and Storage**

- Handling** Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
- Storage.** Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents.

**8. Exposure controls / personal protection**

**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Hexane	TWA: 50 ppm Skin	(Vacated) TWA: 50 ppm (Vacated) TWA: 180 mg/m <sup>3</sup> TWA: 500 ppm TWA: 1800 mg/m <sup>3</sup>	IDLH: 1100 ppm REL = 50 ppm (TWA) REL = 180 mg/m <sup>3</sup> (TWA)	TWA: 50 ppm
Cyclohexane	TWA: 100 ppm	(Vacated) TWA: 300 ppm (Vacated) TWA: 1050 mg/m <sup>3</sup> TWA: 300 ppm TWA: 1050 mg/m <sup>3</sup>	IDLH: 1300 ppm REL = 300 ppm (TWA) REL = 1050 mg/m <sup>3</sup> (TWA)	TWA: 100 ppm

*Legend*

ACGIH - American Conference of Governmental Industrial Hygienists  
 OSHA - Occupational Safety and Health Administration  
 NIOSH: NIOSH - National Institute for Occupational Safety and Health

- Engineering Measures** Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

- Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
- Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.
- Respiratory Protection** Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended Filter type:** low boiling organic solvent. Type AX. Brown. conforming to EN371.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

**Appearance**

**Physical State** Liquid

**Color** Colorless

**Odor** Petroleum distillates

**Odor Threshold** No information available

**Property**

**Melting Point/Range** -40 °C / -40 °F

**Softening Point** No data available

**Boiling Point/Range** 60 - 100 °C / 140 - 212 °F

**Flash Point** -20 °C / -4 °F

**Flammability (liquid)** Highly flammable

**Flammability (solid,gas)** Not applicable

**Explosion Limits** **Lower** 1.1 vol%

**Upper** 7.4 vol%

**Autoignition Temperature** 258 °C / 496.4 °F

**Decomposition Temperature** No data available

**pH** No information available

**Viscosity** 0.57 cSt @ 25°C

**Water Solubility** Insoluble

**Solubility in other solvents** No information available

**Partition Coefficient (n-octanol/water)**

**Component** **log Pow**

Hexane 4.11

Cyclohexane 3.44

**Vapor Pressure** 105 mmHg @ 20°C

**Density / Specific Gravity** 0.700

**Bulk Density** Not applicable

Liquid  
(Air = 1.0)

**Vapor Density** No data available

**Particle characteristics** Not applicable (liquid)

**Other Information**

**Explosive Properties** Vapors may form explosive mixtures with air

## 10. Stability and reactivity

**Reactive Hazard** None known, based on information available

**Stability** Stable under normal conditions.

**Conditions to Avoid** Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible Materials** Strong oxidizing agents

**Hazardous Decomposition Products** Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

## 11. Toxicological information

### Information on expected route of exposure

**Inhalation** Avoid breathing vapors or mists.  
**Ingestion** May be harmful if swallowed. Potential for aspiration if swallowed.  
**Eyes** Avoid contact with eyes. May cause irritation.  
**Skin** Avoid contact with skin. May cause irritation. Prolonged skin contact may defat the skin and produce dermatitis.

### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Naphtha (petroleum), hydrotreated light	LD50 > 5000 mg/kg ( Rat )	LD50 > 3160 mg/kg ( Rabbit )	LC50 = 73680 ppm ( Rat ) 4 h
Hexane	LD50 = 25 g/kg ( Rat )	LD50 = 3000 mg/kg ( Rabbit )	LC50 = 48000 ppm ( Rat ) 4 h
Cyclohexane	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	LC50 > 32880 mg/m <sup>3</sup> ( Rat ) 4 h

**Toxicologically Synergistic Products** No information available

**(b) skin corrosion/irritation;** Category 2

**(c) serious eye damage/irritation;** Based on available data, the classification criteria are not met

**(d) respiratory or skin sensitization;**  
**Respiratory** Based on available data, the classification criteria are not met  
**Skin** Based on available data, the classification criteria are not met

**(e) germ cell mutagenicity;** Based on available data, the classification criteria are not met

**(f) carcinogenicity;** Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen. Petroleum products are known to cause cancer because of carcinogenic components (e.g. benzene). These carcinogenic components may be removed during the refinement process. The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen. This note applies only to certain complex oil derived substances in Annex I

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Naphtha (petroleum), hydrotreated light	64742-49-0	Not listed	Not listed	Not listed	Not listed	Not listed
Hexane	110-54-3	Not listed	Not listed	Not listed	Not listed	Not listed
Cyclohexane	110-82-7	Not listed	Not listed	Not listed	Not listed	Not listed

**(g) reproductive toxicity;** Category 2

**(h) STOT-single exposure;** Category 3  
**Results / Target organs** Central nervous system (CNS).

**(i) STOT-repeated exposure;** Based on available data, the classification criteria are not met

**Target Organs** None known.

**(j) aspiration hazard;** Category 1

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Other Adverse Effects** The toxicological properties have not been fully investigated.

**Endocrine Disrupting Properties** This product does not contain any known or suspected endocrine disruptors.

## 12. Ecological information

**Ecotoxicity**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Naphtha (petroleum), hydrotreated light	Not listed	LC50: = 8.41 mg/L, 96h semi-static, closed (Oncorhynchus mykiss)	Not listed	Not listed
Hexane	Not listed	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	Not listed	EC50: 3.87 mg/L/48h
Cyclohexane	EC50 >500 mg/L/72h	LC50: 48.87 - 68.76 mg/L, 96h static (Poecilia reticulata) LC50: 24.99 - 44.69 mg/L, 96h static (Lepomis macrochirus) LC50: 23.03 - 42.07 mg/L, 96h static (Pimephales promelas) LC50: 3.96 - 5.18 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	EC50 = 0.9 mg/l/48h

**Persistence and Degradability** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
Hexane	4.11
Cyclohexane	3.44

## 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Cyclohexane - 110-82-7	U056	-

## 14. Transport information

**DOT**

**UN-No** UN3295  
**Proper Shipping Name** Hydrocarbons, liquid, n.o.s.

<b>Technical Shipping Name</b>	Petroleum ether, boiling range 60-95°C
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>TDG</b>	
<b>UN-No</b>	UN3295
<b>Proper Shipping Name</b>	Hydrocarbons, liquid, n.o.s.
<b>Technical Shipping Name</b>	Petroleum ether, boiling range 60-95°C
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>IATA</b>	
<b>UN-No</b>	UN3295
<b>Proper Shipping Name</b>	Hydrocarbons, liquid, n.o.s.
<b>Technical Shipping Name</b>	Petroleum ether, boiling range 60-95°C
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>IMDG/IMO</b>	
<b>UN-No</b>	UN3295
<b>Proper Shipping Name</b>	Hydrocarbons, liquid, n.o.s.
<b>Technical Shipping Name</b>	Petroleum ether, boiling range 60-95°C
<b>Hazard Class</b>	3
<b>Packing Group</b>	II

**15. Regulatory Information**

**United States of America Inventory**

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Naphtha (petroleum), hydrotreated light	64742-49-0	X	ACTIVE	-
Hexane	110-54-3	X	ACTIVE	-
Cyclohexane	110-82-7	X	ACTIVE	-

**Legend:**

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)  
 X - Listed  
 - - Not Listed

**TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)** Not applicable

**TSCA 12(b) - Notices of Export** Not applicable

**International Inventories**

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Naphtha (petroleum), hydrotreated light	64742-49-0	X	-	265-151-9	X	-		X	X	KE-25623
Hexane	110-54-3	X	-	203-777-6	X	X	X	X	X	KE-18626
Cyclohexane	110-82-7	X	-	203-806-2	X	X	X	X	X	KE-18562

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

**U.S. Federal Regulations**

**SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold	SARA 313 - Reporting
-----------	--------	----------	----------------------	----------------------

			Values %	thresholds
Hexane	110-54-3	<5	1.0 %	-
Cyclohexane	110-82-7	<1.5	1.0 %	-

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)**

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Cyclohexane	X	1000 lb	-	-

**Clean Air Act**

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Hexane	X		-

**OSHA - Occupational Safety and Health Administration** Not applicable

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Hexane	5000 lb	-	5000 lb 2270 kg
Cyclohexane	1000 lb	-	1000 lb 454 kg

**California Proposition 65** This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Hexane	110-54-3	Male Reproductive	-	Developmental

**U.S. State Right-to-Know Regulations**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Hexane	X	X	X	X	X
Cyclohexane	X	X	X	-	X

**U.S. Department of Transportation**

Reportable Quantity (RQ): Y  
 DOT Marine Pollutant N  
 DOT Severe Marine Pollutant N

**U.S. Department of Homeland Security** This product does not contain any DHS chemicals.

**Other International Regulations**

**Mexico - Grade** Serious risk, Grade 3

**Authorisation/Restrictions according to EU REACH**

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC)

		Annex XIV - Substances Subject to Authorization	Annex XVII - Restrictions on Certain Dangerous Substances	1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Naphtha (petroleum), hydrotreated light	64742-49-0	-	Use restricted. See entry 28. (see link for restriction details) Use restricted. See entry 29. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Hexane	110-54-3	-	Use restricted. See entry 75. (see link for restriction details)	SVHC candidate list - EC 203-777-6 - Specific target organ toxicity after repeated exposure Article 57(f) - human health
Cyclohexane	110-82-7	-	Use restricted. See entry 57. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

**REACH links**

<https://echa.europa.eu/substances-restricted-under-reach>

<https://echa.europa.eu/candidate-list-table>

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Naphtha (petroleum), hydrotreated light	64742-49-0	Listed	Not applicable	Not applicable	Not applicable
Hexane	110-54-3	Listed	Not applicable	Not applicable	Not applicable
Cyclohexane	110-82-7	Listed	Not applicable	Not applicable	Not applicable

**Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?**

Not applicable

**Other International Regulations**

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Naphtha (petroleum), hydrotreated light	64742-49-0	2500 tonne	25000 tonne	Not applicable	Not applicable
Hexane	110-54-3	Not applicable	Not applicable	Not applicable	Annex I - Y42
Cyclohexane	110-82-7	Not applicable	Not applicable	Not applicable	Not applicable

## 16. Other Information

**Prepared By** Product stewardship (Regulatory Affairs)  
Thermo Fisher Scientific  
email - begel.sdsdesk@thermofisher.com

**Creation Date** 19-Nov-2009  
**Revision Date** 14-Mar-2026  
**Print Date** 14-Mar-2026  
**Revision Summary** Updated to the U.S. Department of Labor's Occupational Safety and Health Administration (OSHA) which published its Final Rule in the Federal Register revising the Hazard Communication Standard (HCS/HazCom), 29 CFR 1910.1200 (2024) (HCS §1910.1200, 2024), May 20, 2024, effective July 19, 2024.

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**