

SAFETY DATA SHEET

Creation Date 17-Oct-2000

Revision Date 25-Dec-2021

Revision Number 5

1. Identification

Product Name

2-Methylbutyraldehyde

Cat No. :

AC304470000; AC304470500; AC304472500

CAS No Synonyms

96-17-3 2-Methylbutanal

Recommended Use Uses advised against

Laboratory chemicals. Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

<u>Company</u>

Fisher Scientific Company One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100 Acros Organics One Reagent Lane Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Serious Eye Damage/Eye Irritation Skin Sensitization Specific target organ toxicity (single exposure) Target Organs - Respiratory system. Category 2 Category 2 Category 1 Category 3

Label Elements

Signal Word Danger

Hazard Statements

Highly flammable liquid and vapor May cause an allergic skin reaction Causes serious eye irritation May cause respiratory irritation



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS No	Weight %		
Butanal, 2-methyl-	96-17-3	> 95		

4. First-aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Most important symptoms and effects	None reasonably foreseeable. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	No information available
Flash Point	4 °C / 39.2 °F
Method -	No information available
Autoignition Temperature	240 °C / 464 °F
Explosion Limits Upper Lower Sensitivity to Mechanical Impac Sensitivity to Static Discharge	No data available No data available In No information available No information available

Specific Hazards Arising from the Chemical

Flammable. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

<u>NFPA</u> Health 2	Flammability 3	Instability 1	Physical hazards N/A					
	6. Accidental re	elease measures						
Personal Precautions		on. Use personal protective equip precautionary measures against						
Environmental Precautions								
Methods for Containment and Clea		ontainers for disposal. Soak up w ition. Use spark-proof tools and e						
	7. Handling	and storage						
Handling	Wear personal protective	equipment/face protection. Ensu	re adequate ventilation. Do not					

	get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
Storage.	Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place. Store under an inert atmosphere. Incompatible Materials. Strong oxidizing agents. Strong bases. Strong reducing agents.
8. E	xposure controls / personal protection
Exposure Guidelines	This product does not contain any hazardous materials with occupational exposure limitsestablished by the region specific regulatory bodies.
Engineering Measures	Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment	
Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	No protective equipment is needed under normal use conditions.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.
	Development of the properties

9. PHYSICA	i and chemical properties
Physical State	Liquid
Appearance	Light yellow
Odor	pungent
Odor Threshold	No information available
рН	No information available
Melting Point/Range	No data available
Boiling Point/Range	90 - 92 °C / 194 - 197.6 °F
Flash Point	4 °C / 39.2 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	0.805
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	240 °C / 464 °F
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C5 H10 O
Molecular Weight	86.13

10. Stability and reactivity

Reactive Hazard	None known, based on information available					
Stability	Air sensitive.					
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition. Exposure to air. Incompatible products.					
Incompatible Materials	Strong oxidizing agents, Strong bases, Strong reducing agents					
Hazardous Decomposition Product	s Carbon monoxide (CO), Carbon dioxide (CO ₂)					
Hazardous Polymerization	No information available.					
Hazardous Reactions	None under normal processing.					

11. Toxicological information

Acute Toxicity

Product Information

Component Information									
Componer		LD50 Oral		LD50 Dermal	LC50	Inhalation			
Butanal, 2-me		LD50 = 6400 mg/kg (F	Rat) LD50 =	LD50 = 5400 mg/kg (Rabbit)		5 mg/L (Rat)4 h			
Toxicologically Syn Products	ergistic	No information ava	No information available						
Delayed and immed	liate effects	as well as chronic effe	cts from short a	nd long-term expos	ure				
Irritation Irritating to eyes and respiratory system									
Sensitization		May cause sensitiz	zation by skin cor	itact					
Carcinogenicity		The table below in	dicates whether e	each agency has liste	ed any ingredient	as a carcinogen.			
Component	CAS N	o IARC	NTP	ACGIH	OSHA	Mexico			
Butanal, 2-methyl-	96-17-3		Not listed	Not listed	Not listed	Not listed			
Mutagenic Effects Reproductive Effec	ts		No information available						
Developmental Effe	ects	No information ava	No information available.						
Teratogenicity		No information ava	ailable.						
STOT - single exposureRespiratory systemSTOT - repeated exposureNone known									
Aspiration hazard		No information ava	ailable						
Symptoms / effects delayed	s,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, or pain, muscle pain or flushing								
Endocrine Disrupto	or Informatio	on No information ava	No information available						
Other Adverse Effe	cts	The toxicological p	The toxicological properties have not been fully investigated.						
		12. Ecolo	ogical info	rmation					
Ecotoxicity									

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following

substances which are hazardous for the environment.

Component	Freshwater Algae		Freshwater Fish	Microtox	Water Flea		
Butanal, 2-methyl-	Not listed		LC50: 9.4 - 10.6 mg/L, 96h flow-through (Pimephales promelas)	Not listed	Not listed		
Persistence and Degradability Soluble in water Persistence is unlikely based on information available.							
Bioaccumulation/Accum	nulation	No information available.					
Mobility		Will likely be	be mobile in the environment due to its water solubility.				
13. Disposal considerations							
hazardous wa			aste generators must determin vaste. Chemical waste genera ardous waste regulations to e	ators must also consult	local, regional, and		

	14. Transport information
DOT	
UN-No	UN3371
Proper Shipping Name	2-METHYLBUTANAL
Hazard Class	3
Packing Group	ll
TDG	
UN-No	UN3371
Proper Shipping Name	2-METHYLBUTANAL
Hazard Class	3
Packing Group	III
IATA	
UN-No	UN3371
Proper Shipping Name	2-METHYLBUTANAL
Hazard Class	3
Packing Group	ll
IMDG/IMO	
UN-No	UN3371
Proper Shipping Name	2-METHYLBUTANAL
Hazard Class	3
Packing Group	II
	15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Butanal, 2-methyl-	96-17-3	Х	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710) X - Listed '-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Butanal, 2-methyl-	96-17-3	Х	-	202-485-6	Х	Х	Х	Х	Х	KE-23535

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313	Not applicable
SARA 311/312 Hazard Categories	See section 2 for more information
CWA (Clean Water Act)	Not applicable
Clean Air Act	Not applicable
OSHA - Occupational Safety and Health Administration	Not applicable
CERCLA	Not applicable

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Butanal, 2-methyl-	Х	Х	Х	-	Х
				•	

U.S. Department of Transportation

Reportable Quantity (RQ):	Ν
DOT Marine Pollutant	Ν
DOT Severe Marine Pollutant	Ν
U.S. Department of Homeland Security	This product does not contain any DHS chemicals.
Other International Regulations	

Mexico - Grade

No information available

Authorisation/Restrictions according to EU REACH

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Butanal, 2-methyl-	96-17-3	Not applicable	Not applicable	Not applicable	Not applicable
Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Butanal, 2-methyl-	96-17-3	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date Revision Date Print Date Revision Summary	17-Oct-2000 25-Dec-2021 25-Dec-2021 This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS