

SAFETY DATA SHEET

Creation Date 27-Apr-2009

Revision Date 19-Dec-2025

Revision Number 13

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard 2024 (29 CFR 1910.1200)

1. Identification

Product Name Methanol

Cat No. : AC327900000; AC327900010; AC327900025

CAS No 67-56-1
Synonyms Methyl alcohol

Recommended Use Laboratory chemicals.
Uses advised against .

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous according to [US] OSHA (29 CFR 1910.1200, 2024)

Flammable liquids	Category 2
Acute oral toxicity	Category 3
Acute dermal toxicity	Category 3
Acute Inhalation Toxicity - Vapors	Category 3
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Optic nerve, Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Kidney, Liver, spleen, Blood.	

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
Causes damage to organs
Causes damage to organs through prolonged or repeated exposure
Toxic if swallowed, in contact with skin or if inhaled

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Wear protective gloves/protective clothing/eye protection/face protection
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground and bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Keep cool
Take action to prevent static discharges
Use non-sparking tools

Response

IF exposed: Call a POISON CENTER or doctor

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor

Skin

Call a POISON CENTER or doctor if you feel unwell
Take off contaminated clothing and wash before reuse
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor
Rinse mouth

Fire

In case of fire: Use CO₂, dry chemical, or foam to extinguish

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Hazards classified under paragraph (d)(1)(ii) of 1910.1200**

No information available

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS.
WARNING. Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/information on Ingredients

Component	CAS No	Weight %
Methyl alcohol	67-56-1	>95

4. First-aid measures

General Advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Most important symptoms and effects	Difficulty in breathing. May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point	10 °C / 50 °F
Method -	CC (closed cup) Abel-Pensky (DIN 51755) Directive 84/449/EEC, A.9
Autoignition Temperature	455 °C / 851 °F
Explosion Limits	
Upper	31.00 vol %
Lower	6.0 vol %
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO). Formaldehyde.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
2Flammability
3Instability
0Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
Environmental Precautions	Should not be released into the environment. See Section 12 for additional Ecological Information.
Methods for Containment and Clean Up	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and Storage

Handling	Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
Storage.	Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammables area. Incompatible Materials. Strong oxidizing agents. Strong acids. Acid anhydrides. Acid chlorides. Strong bases. Metals. Peroxides.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m ³ Skin TWA: 200 ppm TWA: 260 mg/m ³	IDLH: 6000 ppm REL = 200 ppm (TWA) REL = 260 mg/m ³ (TWA) STEL: 250 ppm STEL: 325 mg/m ³	TWA: 200 ppm STEL: 250 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
 OSHA - Occupational Safety and Health Administration
 NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.
-----------------------------	--

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: low boiling organic solvent. Type AX. Brown. conforming to EN371.

Hygiene Measures When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. Physical and chemical properties

Appearance

Physical State Liquid

Color Colorless

Odor Alcohol-like

Odor Threshold No information available

Property

Melting Point/Range -98 °C / -144.4 °F

Softening Point No data available

Boiling Point/Range 64.7 °C / 148.5 °F

Flash Point 10 °C / 50 °F

Flammability (liquid) Highly flammable

Flammability (solid,gas) Not applicable

Explosion Limits

Lower 6 vol%

Upper 31 vol%

Autoignition Temperature 455 °C / 851 °F

Decomposition Temperature No data available

pH No information available

Viscosity 0.55 cP at 20 °C

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component **log Pow**

Methyl alcohol -0.74

Vapor Pressure 128 hPa @ 20 °C

Density / Specific Gravity 0.791

Bulk Density Not applicable

Vapor Density 1.11

Particle characteristics Not applicable (liquid)

Remarks

• Method

@ 760 mmHg

Method - CC (closed cup) Abel-Pensky (DIN 51755) Directive 84/449/EEC, A.9

On basis of test data

Liquid

Liquid
(Air = 1.0)

Other Information

Molecular Formula C H4 O

Molecular Weight 32.04

VOC Content(%) 100

Explosive Properties Not explosive Vapors may form explosive mixtures with air

Evaporation Rate 5.2 (ether = 1)

Surface tension 0.02255 N/m @ 20°C

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides, Strong bases,

Metals, Peroxides

Hazardous Decomposition Products Carbon monoxide (CO), Formaldehyde**Hazardous Polymerization** Hazardous polymerization does not occur.**Hazardous Reactions** None under normal processing.

11. Toxicological information

Information on expected route of exposure

Inhalation Avoid breathing vapors or mists. Harmful by inhalation.
Ingestion May be harmful if swallowed.
Eyes Avoid contact with eyes.
Skin Avoid contact with skin. Prolonged skin contact may defat the skin and produce dermatitis. Harmful in contact with skin.

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h

Toxicologically Synergistic Products Ethanol**(b) skin corrosion/irritation;** Based on available data, the classification criteria are not met**(c) serious eye damage/irritation;** Based on available data, the classification criteria are not met**(d) respiratory or skin sensitization;****Respiratory**

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Methyl alcohol 67-56-1 (>95)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met**(f) carcinogenicity;** Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl alcohol	67-56-1	Not listed				

(g) reproductive toxicity; Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Methyl alcohol 67-56-1 (>95)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

Developmental Effects Component substance is listed on California Proposition 65 as a developmental hazard.**(h) STOT-single exposure;** Category 1**Results / Target organs** Optic nerve, Central nervous system (CNS).

- (i) **STOT-repeated exposure;** Based on available data, the classification criteria are not met
- Target Organs** None known.
- (j) **aspiration hazard;** Based on available data, the classification criteria are not met
- Symptoms / effects,both acute and delayed** May cause blindness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
- Other Adverse Effects** The toxicological properties have not been fully investigated.
- Endocrine Disrupting Properties** This product does not contain any known or suspected endocrine disruptors.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methyl alcohol	-0.74

13. Disposal considerations

Waste Disposal Methods Should not be released into the environment.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

14. Transport information

DOT

UN-No UN1230
Proper Shipping Name METHANOL
Hazard Class 3
Packing Group II

TDG

UN-No UN1230
Proper Shipping Name METHANOL
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

IATA

UN-No UN1230
Proper Shipping Name METHANOL
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

IMDG/IMO

UN-No UN1230

Proper Shipping Name METHANOL
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

15. Regulatory Information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Methyl alcohol	67-56-1	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT) Not applicable

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Methyl alcohol	67-56-1	X	-	200-659-6	X	X	X	X	X	KE-23193

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting thresholds
Methyl alcohol	67-56-1	>95	1.0 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act) Not applicable

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Methyl alcohol	5000 lb	-	5000 lb 2270 kg

California Proposition 65 This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Methyl alcohol	67-56-1	Developmental	-	Developmental

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl alcohol	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y

DOT Marine Pollutant N

DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	67-56-1	-	Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable

16. Other Information

Prepared By	Product stewardship (Regulatory Affairs) Thermo Fisher Scientific email - begel.sdsdesk@thermofisher.com
Creation Date	27-Apr-2009
Revision Date	19-Dec-2025
Print Date	19-Dec-2025
Revision Summary	Updated to the U.S. Department of Labor's Occupational Safety and Health Administration (OSHA) which published its Final Rule in the Federal Register revising the Hazard Communication Standard (HCS/HazCom), 29 CFR 1910.1200 (2024) (HCS §1910.1200, 2024), May 20, 2024, effective July 19, 2024.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS