

SAFETY DATA SHEET

Creation Date 21-Oct-2014 Revision Date 19-Dec-2025 Revision Number 5

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard 2024 (29 CFR 1910.1200)

1. Identification

Product Name 3-Methyl-2-butenal

Cat No.: AC370180000; AC370180050; AC370180250; AC370181000

CAS No 107-86-8

Synonyms 3-Methylcrotonaldehyde; Prenal; 3,3-Dimethylacrolein

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous according to [US] OSHA (29 CFR 1910.1200, 2024)

Flammable liquids

Acute oral toxicity

Category 4

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Category 1

Serious Eye Damage/Eye Irritation

Skin Sensitization

Category 1

Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Flammable liquid and vapor Harmful if swallowed Causes severe skin burns and eye damage May cause an allergic skin reaction Toxic if inhaled



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection

Contaminated work clothing should not be allowed out of the workplace

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground and bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Keep cool

Take action to prevent static discharges

Use non-sparking tools

Response

Immediately call a POISON CENTER or doctor

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Skir

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Ingestion

Rinse mouth

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam to extinguish

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available

3. Composition/information on Ingredients

Component	CAS No	Weight %	
2-Butenal, 3-methyl-	107-86-8	>95	

4. First-aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact In the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give

artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is

required. If not breathing, give artificial respiration.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Difficulty in breathing. Causes burns by all exposure routes. May cause allergic skin reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle

pain or flushing

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point 33 °C / 91.4 °F

Method - No information available

Autoignition Temperature

Explosion Limits

No information available

UpperNo data availableLowerNo data available

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition can lead to release of irritating gases and vapors.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Revision Date 19-Dec-2025 3-Methyl-2-butenal

NFPA

Health **Flammability** Instability Physical hazards N/A

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Should not be released into the environment. Do not flush into surface water or sanitary

Environmental Precautions

sewer system. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and Storage

Handling

Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Storage.

Corrosives area. Keep away from heat, sparks and flame. To maintain product quality: Keep refrigerated. Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Acids. Bases.

8. Exposure controls / personal protection

Exposure Guidelines

This product does not contain any hazardous materials with occupational exposure limitsestablished by the region specific regulatory bodies.

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Personal Protective Equipment

Tight sealing safety goggles. Face protection shield. **Eye/face Protection**

Wear appropriate protective gloves and clothing to prevent skin exposure. Skin and body protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection**

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Organic gases and vapours filter. Type A. Brown. conforming to EN14387. **Recommended Filter type:**

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Physical and chemical properties

Appearance

Physical State Liquid Color Clear

No information available Odor No information available **Odor Threshold**

Property Values • Method

Melting Point/RangeNo data availableSoftening PointNo data available

Boiling Point/Range 132 - 133 °C / 269.6 - 271.4 °F

Flash Point 33 °C / 91.4 °F Method - No information available

Flammability (liquid) Flammable On basis of test data Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Autoignition TemperatureNo data availableDecomposition TemperatureNo data availablepHNo information availableViscosityNo data available

Water Solubility Soluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow 2-Butenal, 3-methyl- 0.53

Vapor Pressure No data available

Density / Specific Gravity 0.880

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)Particle characteristicsNot applicable (liquid)

Other Information

Molecular Formula C5 H8 O Molecular Weight 84.12

Explosive Properties explosive air/vapour mixtures possible

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Air sensitive.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to air.

Incompatible Materials Strong oxidizing agents, Acids, Bases

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Thermal decomposition can lead to release

of irritating gases and vapors

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Information on expected route of exposure

Inhalation Harmful by inhalation.

Ingestion Ingestion causes burns of the upper digestive and respiratory tracts. Can burn mouth,

throat, and stomach. Harmful if swallowed.

Eyes Causes burns. Corrosive to the eyes and may cause severe damage including blindness.

Risk of serious damage to eyes.

Skin Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Causes burns.

Revision Date 19-Dec-2025 3-Methyl-2-butenal

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
2-Butenal, 3-methyl-	650 mg/kg (Rat)	LD50 = 3400 mg/kg (Rat)	LC50 = 3.7 mg/L (Rat) 4 h		

Toxicologically Synergistic

No information available

Products

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

No data available Respiratory Skin Category 1

May cause sensitization by skin contact

No data available (e) germ cell mutagenicity;

(f) carcinogenicity;

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
2-Butenal, 3-methyl-	107-86-8	Not listed				

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

No information available. **Target Organs**

No data available (j) aspiration hazard;

Other Adverse Effects The toxicological properties have not been fully investigated.

delayed

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Other Adverse Effects The toxicological properties have not been fully investigated.

Endocrine Disrupting Properties This product does not contain any known or suspected endocrine disruptors.

12. Ecological information

Ecotoxicity

Do not empty into drains. Contains a substance which is: Harmful to aquatic organisms. The product contains following

Revision Date 19-Dec-2025 3-Methyl-2-butenal

substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
2-Butenal, 3-methyl-	EC50: = 22.9 mg/L, 96h (Desmodesmus subspicatus) EC50: = 19.9 mg/L, 72h (Desmodesmus subspicatus)	Not listed	EC50 = 106 mg/L 30 min EC50 = 148 mg/L 15 min EC50 = 178 mg/L 17 h	EC50: = 13.5 mg/L, 48h (Daphnia magna)

Persistence and Degradability

Persistence is unlikely

Bioaccumulation/ Accumulation

No information available.

Mobility

. Will likely be mobile in the environment due to its water solubility.

Component	log Pow	
2-Butenal, 3-methyl-	0.53	

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN2920

CORROSIVE LIQUIDS, FLAMMABLE, N.O.S. **Proper Shipping Name**

2-Butenal, 3-methyl-**Technical Shipping Name**

Hazard Class 8 3 **Subsidiary Hazard Class** Ш **Packing Group**

TDG

UN-No UN2920

Proper Shipping Name Corrosive liquid, flammable, n.o.s.

Technical Shipping Name 2-Butenal, 3-methyl-

Hazard Class Subsidiary Hazard Class 3 **Packing Group** Ш

IATA UN-No

UN2920

Proper Shipping Name Corrosive liquid, flammable, n.o.s.

Technical Shipping Name 2-Butenal, 3-methyl-

Hazard Class 8 **Subsidiary Hazard Class** 3 **Packing Group** Ш

IMDG/IMO

UN-No UN2920

Proper Shipping Name Corrosive liquid, flammable, n.o.s.

Technical Shipping Name 2-Butenal, 3-methyl-

Hazard Class Subsidiary Hazard Class 3 **Packing Group** Ш

15. Regulatory Information

United States of America Inventory

Component	CAS No	TSCA TSCA Inventory notification -		TSCA - EPA Regulatory
-			Active-Inactive	Flags

2-Butenal, 3-methyl-	107-86-8	X	ACTIVE	PMN

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

PMN - Indicates a commenced PMN substance

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

	Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Г	2-Butenal, 3-methyl-	107-86-8	X	-	203-527-6	X	X	X	Х	X	-

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know

Regulations

Not applicable

U.S. Department of Transportation

Reportable Quantity (RQ):

DOT Marine Pollutant

DOT Severe Marine Pollutant

N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	J	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
2-Butenal, 3-methyl-	107-86-8	-	-	-

Not applicable

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
2-Butenal, 3-methyl-	107-86-8	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Other International Regulations

1	Component	CAS No	Seveso III Directive	Seveso III Directive	Rotterdam	Basel Convention
1			(2012/18/EC) -	(2012/18/EC) -	Convention (PIC)	(Hazardous Waste)
1			Qualifying Quantities	Qualifying Quantities		
1			for Major Accident	for Safety Report		
L			Notification	Requirements		
	2-Butenal, 3-methyl-	107-86-8	Not applicable	Not applicable	Not applicable	Not applicable

1/ Other lafe was atten-	
16. Other Information	

Prepared By Product stewardship (Regulatory Affairs)

Thermo Fisher Scientific

email - begel.sdsdesk@thermofisher.com

 Creation Date
 21-Oct-2014

 Revision Date
 19-Dec-2025

 Print Date
 19-Dec-2025

Revision Summary Updated to the U.S. Department of Labor's Occupational Safety and Health Administration

(OSHA) which published its Final Rule in the Federal Register revising the Hazard Communication Standard (HCS/HazCom), 29 CFR 1910.1200 (2024) (HCS §1910.1200,

2024), May 20, 2024, effective July 19, 2024.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS