

# **SAFETY DATA SHEET**

Creation Date 21-Oct-2014 Revision Date 25-Dec-2021 Revision Number 4

1. Identification

Product Name 3-Methyl-2-butenal

Cat No.: AC370180000; AC370180050; AC370180250; AC370181000

**CAS No** 107-86-8

Synonyms 3-Methylcrotonaldehyde; Prenal; 3,3-Dimethylacrolein

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

### Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

## 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Acute oral toxicity

Category 4

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Skin Sensitization

Category 1

Category 1

Category 1

### Label Elements

## Signal Word

Danger

#### **Hazard Statements**

Flammable liquid and vapor Harmful if swallowed

\_\_\_\_\_

Causes severe skin burns and eye damage May cause an allergic skin reaction Toxic if inhaled



## **Precautionary Statements**

### Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection

Contaminated work clothing should not be allowed out of the workplace

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

### Response

Immediately call a POISON CENTER or doctor/physician

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

If skin irritation or rash occurs: Get medical advice/attention

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

## Ingestion

Rinse mouth

Do NOT induce vomiting

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

## Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

## **Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

None identified

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
2-Butenal, 3-methyl-	107-86-8	>95

## 4. First-aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact In the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

**Inhalation** Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give

artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is

required. If not breathing, give artificial respiration.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Difficulty in breathing. Causes burns by all exposure routes. May cause allergic skin reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle

pain or flushing

Notes to Physician Treat symptomatically

## 5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point 33 °C / 91.4 °F

Method - No information available

**Autoignition Temperature** 

**Explosion Limits** 

No information available

Upper No data available
Lower No data available

Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

#### Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Thermal decomposition can lead to release of irritating gases and vapors.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

HealthFlammabilityInstabilityPhysical hazards321N/A

Revision Date 25-Dec-2021 3-Methyl-2-butenal

## Accidental release measures

**Personal Precautions** 

Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Should not be released into the environment. Do not flush into surface water or sanitary

**Environmental Precautions** sewer system. See Section 12 for additional Ecological Information.

Up

Methods for Containment and Clean Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

Handling

Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Storage.

Corrosives area. Keep away from heat, sparks and flame. To maintain product quality: Keep refrigerated. Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Acids. Bases.

## Exposure controls / personal protection

**Exposure Guidelines** 

This product does not contain any hazardous materials with occupational exposure limitsestablished by the region specific regulatory bodies.

**Engineering Measures** 

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

#### **Personal Protective Equipment**

**Eye/face Protection** Tight sealing safety goggles. Face protection shield.

Wear appropriate protective gloves and clothing to prevent skin exposure. Skin and body protection

**Respiratory Protection** 

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures** 

## 9. Physical and chemical properties

**Physical State** Liquid **Appearance** Clear

Odor No information available **Odor Threshold** No information available No information available Melting Point/Range No data available

**Boiling Point/Range** 132 - 133 °C / 269.6 - 271.4 °F

33 °C / 91.4 °F **Flash Point Evaporation Rate** No information available Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper No data available No data available Lower

Vapor PressureNo information availableVapor DensityNo information available

Specific Gravity 0.880

Solubility
Partition coefficient; n-octanol/water
No information available
No data available

Autoignition TemperatureNo information availableDecomposition TemperatureNo information availableViscosityNo information available

Molecular Formula C5 H8 O Molecular Weight 84.12

## 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Air sensitive.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to air.

Incompatible Materials Strong oxidizing agents, Acids, Bases

Hazardous Decomposition Products Carbon monoxide (CO<sub>2</sub>), Carbon dioxide (CO<sub>2</sub>), Thermal decomposition can lead to release

of irritating gases and vapors

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

## 11. Toxicological information

#### **Acute Toxicity**

### Product Information

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
2-Butenal, 3-methyl-	650 mg/kg (Rat)	LD50 = 3400 mg/kg (Rat)	LC50 = 3.7 mg/L (Rat) 4 h

Toxicologically Synergistic No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization May cause sensitization by skin contact

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
2-Butenal, 3-methyl-	107-86-8	Not listed				

Mutagenic Effects No information available

Reproductive EffectsNo information available.Developmental EffectsNo information available.

**Teratogenicity** No information available.

STOT - single exposure None known STOT - repeated exposure None known

Revision Date 25-Dec-2021 3-Methyl-2-butenal

**Aspiration hazard** No information available

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

## 12. Ecological information

#### **Ecotoxicity**

Do not empty into drains. Contains a substance which is:. Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

Co	mponent	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
2-Buter	nal, 3-methyl-	EC50: = 22.9 mg/L, 96h (Desmodesmus subspicatus) EC50: = 19.9 mg/L, 72h (Desmodesmus subspicatus)	Not listed	EC50 = 106 mg/L 30 min EC50 = 148 mg/L 15 min EC50 = 178 mg/L 17 h	EC50: = 13.5 mg/L, 48h (Daphnia magna)

Persistence and Degradability Persistence is unlikely

**Bioaccumulation/ Accumulation** No information available.

**Mobility** . Will likely be mobile in the environment due to its water solubility.

Component	log Pow	
2-Butenal, 3-methyl-	0.53	

## 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

## Transport information

DOT

**UN-No** UN2920

**Proper Shipping Name** CORROSIVE LIQUIDS, FLAMMABLE, N.O.S.

**Technical Name** 2-Butenal, 3-methyl-

**Hazard Class** 3 **Subsidiary Hazard Class** Ш **Packing Group** 

TDG

**UN-No** UN2920

**Proper Shipping Name** Corrosive liquid, flammable, n.o.s.

**Hazard Class Subsidiary Hazard Class** 3 **Packing Group** Ш

IATA

**UN-No** UN2920

**Proper Shipping Name** Corrosive liquid, flammable, n.o.s.

**Hazard Class Subsidiary Hazard Class** 3

Packing Group

IMDG/IMO

**UN-No** UN2920

**Proper Shipping Name** Corrosive liquid, flammable, n.o.s.

Ш

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

## 15. Regulatory information

### United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
2-Butenal, 3-methyl-	107-86-8	Χ	ACTIVE	PMN

#### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

PMN - Indicates a commenced PMN substance

TSCA 12(b) - Notices of Export Not applicable

### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
2-Butenal, 3-methyl-	107-86-8	Х	-	203-527-6	Χ	Χ	Х	Х	Χ	-

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

### U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** - Occupational Safety and

Health Administration

Not applicable

CERCLA Not applicable

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know

Regulations

Not applicable

## **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

**U.S. Department of Homeland**This product does not contain any DHS chemicals.

Security

Other International Regulations

2-Butenal, 3-methyl-

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
2-Butenal, 3-methyl-	107-86-8	Listed	Not applicable	Not applicable	Not applicable
Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)

16	Othe	r info	rmati	on
	) ()  (	<del>,</del>      (	шиан	

Prepared By Regulatory Affairs

107-86-8

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

Not applicable

 Creation Date
 21-Oct-2014

 Revision Date
 25-Dec-2021

 Print Date
 25-Dec-2021

**Revision Summary**This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Not applicable

Not applicable

Not applicable

Harmonized System of Classification and Labeling of Chemicals (GHS).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**