

SAFETY DATA SHEET

Creation Date 01-Sep-2009

Revision Date 19-Dec-2025

Revision Number 8

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard 2024 (29 CFR 1910.1200)

1. Identification

Product Name Isopropanol

Cat No. : AC383910000; AC383910010; AC383910025

CAS No 67-63-0
Synonyms 2-Propanol; IPA; Isopropyl alcohol; Propan-2-ol; Isopropanol

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous according to [US] OSHA (29 CFR 1910.1200, 2024)

Flammable liquids	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Kidney, Liver.	

Label Elements

Signal Word
Danger

Hazard Statements

Highly flammable liquid and vapor
 Causes serious eye irritation
 May cause respiratory irritation
 May cause drowsiness or dizziness
 May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Keep container tightly closed
 Ground and bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting equipment
 Wear protective gloves/protective clothing/eye protection/face protection
 Keep cool
 Take action to prevent static discharges
 Use non-sparking tools

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing
 Call a POISON CENTER or doctor if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO₂, dry chemical, or foam to extinguish

Storage

Store in a well-ventilated place. Keep container tightly closed
 Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available

3. Composition/information on Ingredients

Component	CAS No	Weight %
Isopropyl alcohol	67-63-0	>95

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
Inhalation	Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.
Ingestion	Do NOT induce vomiting. Get medical attention.
Most important symptoms and effects	Difficulty in breathing. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point	12 °C / 53.6 °F
Method -	Abel Closed Cup (BS 2000 Part 170, IP 170, AS/NZS 2106)
Autoignition Temperature	425 °C / 797 °F
Explosion Limits	
Upper	12 vol %
Lower	2 vol %
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). peroxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.
Environmental Precautions	Should not be released into the environment. See Section 12 for additional Ecological Information.
Methods for Containment and Clean Up	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Use

spark-proof tools and explosion-proof equipment. Keep in suitable, closed containers for disposal.

7. Handling and Storage

Handling	Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.
Storage.	Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place. Incompatible Materials. Strong oxidizing agents. Acids. Halogens. Acid anhydrides.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³	IDLH: 2000 ppm REL = 400 ppm (TWA) REL = 980 mg/m ³ (TWA) STEL: 500 ppm STEL: 1225 mg/m ³	TWA: 200 ppm STEL: 400 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
OSHA - Occupational Safety and Health Administration
NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures	Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.
-----------------------------	--

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Recommended Filter type:	Organic gases and vapours filter. Type A. Brown. conforming to EN14387.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance	
Physical State	Liquid
Color	Colorless
Odor	Alcohol-like
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>• Method</u>
Melting Point/Range	-89.5 °C / -129.1 °F		
Softening Point	No data available		
Boiling Point/Range	81 - 83 °C / 177.8 - 181.4 °F	@ 760 mmHg	
Flash Point	12 °C / 53.6 °F	Method - Abel Closed Cup (BS 2000 Part 170, IP 170, AS/NZS 2106)	
Flammability (liquid)	Highly flammable	On basis of test data	
Flammability (solid,gas)	Not applicable	Liquid	
Explosion Limits	Lower 2 Vol% Upper 12 Vol%		
Autoignition Temperature	425 °C / 797 °F	ASTM E-659	
Decomposition Temperature	No data available		
pH	7	1% aq. sol	
Viscosity	2.27 mPa.s at 20 °C		
Water Solubility	Miscible		
Solubility in other solvents	No information available		
Partition Coefficient (n-octanol/water)			
Component	log Pow		
Isopropyl alcohol	0.05		
Vapor Pressure	43 mmHg @ 20 °C		
Density / Specific Gravity	0.785	ASTM D-4052	
Bulk Density	Not applicable	Liquid	
Vapor Density	2.1 @ 20 °C / 68 °F	(Air = 1.0)	
Particle characteristics	Not applicable (liquid)		
Other Information			
Molecular Formula	C3 H8 O		
Molecular Weight	60.1		
VOC Content(%)	100% (Organic Carbon (by mass) = 59.9 %) (EC/1999/13)		
Explosive Properties	Not explosive explosive air/vapour mixtures possible Vapors may form explosive mixtures with air		
Evaporation Rate	1.7 - ASTM D 3539 (Butyl acetate = 1.0)		
Thermal conductivity	0.137 W/m °C at 20 °C / 68 °F		
Refractive index	1.377 at 20 °C / 68 °F (ASTM D-1218)		
Surface tension	22.7 mN/m at 20 °C / 68 °F		
Coefficient of expansion	0.0009 / °C		
Specific heat capacity	3 kJ/kg °C at 20 °C / 68 °F		
Dielectric constant	18.6 at 20 °C / 68 °F		
Heat of vapourisation	665 J/g		

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Acids, Halogens, Acid anhydrides
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂), peroxides
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Information on expected route of exposure

Inhalation	May be harmful if inhaled. May cause drowsiness and dizziness. May cause irritation of respiratory tract.
Ingestion	May cause central nervous system effects. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Eyes	Irritating to eyes.
Skin	Irritating to skin. May be harmful in contact with skin.

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5045 mg/kg (Rat) 3600 mg/kg (Mouse)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;
Respiratory Based on available data, the classification criteria are not met
Skin Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met
 The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Isopropyl alcohol	67-63-0	Not listed				

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3
Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met
Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects,both acute and delayed May cause central nervous system depression. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Other Adverse Effects The toxicological properties have not been fully investigated.

Endocrine Disrupting Properties This product does not contain any known or suspected endocrine disruptors.

12. Ecological information

Ecotoxicity

. Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 10000000 µg/L, 96h (Daphnia)	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Isopropyl alcohol	0.05

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1219
 Proper Shipping Name Isopropanol
 Hazard Class 3
 Packing Group II

TDG

UN-No UN1219
 Proper Shipping Name ISOPROPANOL
 Hazard Class 3
 Packing Group II

IATA

UN-No UN1219
 Proper Shipping Name Isopropanol
 Hazard Class 3
 Packing Group II

IMDG/IMO

UN-No UN1219
 Proper Shipping Name Isopropanol (Isopropyl alcohol)
 Hazard Class 3
 Packing Group II

15. Regulatory Information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Isopropyl alcohol	67-63-0	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT) Not applicable

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Isopropyl alcohol	67-63-0	X	-	200-661-7	X	X	X	X	X	KE-29363

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting thresholds
Isopropyl alcohol	67-63-0	>95	1.0 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

California Proposition 65 This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isopropyl alcohol	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): N

DOT Marine Pollutant N

DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Isopropyl alcohol	67-63-0	-	Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Isopropyl alcohol	67-63-0	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Isopropyl alcohol	67-63-0	Not applicable	Not applicable	Not applicable	Annex I - Y42

16. Other Information

Prepared By

Product stewardship (Regulatory Affairs)
Thermo Fisher Scientific
email - begel.sdsdesk@thermofisher.com

Creation Date

01-Sep-2009

Revision Date

19-Dec-2025

Print Date

19-Dec-2025

Revision Summary

Updated to the U.S. Department of Labor's Occupational Safety and Health Administration (OSHA) which published its Final Rule in the Federal Register revising the Hazard Communication Standard (HCS/HazCom), 29 CFR 1910.1200 (2024) (HCS §1910.1200, 2024), May 20, 2024, effective July 19, 2024.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS