

# **SAFETY DATA SHEET**

Creation Date 25-May-2009 Revision Date 26-Dec-2021 Revision Number 6

1. Identification

Product Name 1-Chlorobutane

Cat No.: AC425880000; AC425880010; AC425880025

CAS No 109-69-3 Synonyms n-Butyl chloride

Recommended Use Research and development.

Uses advised against All other uses.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2
Aspiration Toxicity Category 1

Label Elements

**Signal Word** 

Danger

**Hazard Statements** 

Highly flammable liquid and vapor

May be fatal if swallowed and enters airways



### **Precautionary Statements**

#### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep cool

**Disposal** 

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
1-Chlorobutane	109-69-3	>95

### 4. First-aid measures

General Advice If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur. Risk of serious damage to the lungs (by aspiration).

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call

a physician or poison control center immediately. If vomiting occurs naturally, have victim

lean forward.

Most important symptoms and

effects

Notes to Physician

None reasonably foreseeable. Inhalation of high vapor concentrations may cause

symptoms like headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

Revision Date 26-Dec-2021 1-Chlorobutane

# 5. Fire-fighting measures

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

**Unsuitable Extinguishing Media** No information available

-12 °C / 10.4 °F **Flash Point** 

Method -No information available

**Autoignition Temperature** 245 °C / 473 °F

**Explosion Limits** 

Upper 10.1 vol % Lower 1.0 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

#### Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2). Hydrogen chloride gas.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
3	3	0	N/A

### Accidental release measures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all **Personal Precautions** 

sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions** 

Should not be released into the environment. Do not flush into surface water or sanitary

sewer system.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Up

Handling Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid

ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Take precautionary measures against static discharges.

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Storage.

Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents.

Strong bases.

## 8. Exposure controls / personal protection

This product does not contain any hazardous materials with occupational exposure **Exposure Guidelines** 

limitsestablished by the region specific regulatory bodies.

**Engineering Measures** Ensure that eyewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting equipment.

Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# Physical and chemical properties

Physical State Liquid Appearance Colorless

Odor No information available
Odor Threshold No information available
pH No information available

Melting Point/Range -123 °C / -189.4 °F

**Boiling Point/Range** 77 - 78 °C / 170.6 - 172.4 °F @ 760 mmHg

Flash Point -12 °C / 10.4 °F
Evaporation Rate No information available

Flammability (solid, gas)

Not applicable

Flammability or explosive limits

 Upper
 10.1 vol %

 Lower
 1.0 vol %

 Vapor Pressure
 108 mbar @ 20 °C

 Vapor Density
 3.19 (Air = 1.0)

Specific Gravity 0.880

SolubilityNo information availablePartition coefficient; n-octanol/waterNo data availableAutoignition Temperature245 °C / 473 °FDecomposition TemperatureNo information availableViscosity0.45 mPa.s (20°C)

Molecular FormulaC4 H9 ClMolecular Weight92.57

### 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** No information available.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong bases

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen chloride gas

Revision Date 26-Dec-2021 1-Chlorobutane

Hazardous polymerization does not occur. **Hazardous Polymerization** 

**Hazardous Reactions** None under normal processing.

# 11. Toxicological information

**Acute Toxicity** 

**Product Information Component Information**  See actual entry in RTECS for complete information.

Component LD50 Oral		LD50 Dermal	LC50 Inhalation	
1-Chlorobutane	LD50 = 2670 mg/kg (Rat)	LD50 > 20000 mg/kg ( Rabbit )	LC50 > 7.74 mg/L (Rat) 4 h	

**Toxicologically Synergistic** 

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
1-Chlorobutane	109-69-3	Not listed				

Mutagenic effects have occurred in experimental animals. **Mutagenic Effects** 

**Reproductive Effects** No information available.

No information available. **Developmental Effects** 

**Teratogenicity** No information available.

STOT - single exposure None known STOT - repeated exposure None known

**Aspiration hazard** Category 1

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** Tumorigenic effects have been reported in experimental animals.

# 12. Ecological information

#### **Ecotoxicity**

Do not empty into drains. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
1-Chlorobutane	EC50: > 450 mg/L, 72h	LC50: = 71.4 mg/L, 96h	EC50 = 485 mg/L 5 min	EC50: = 3020 mg/L, 48h
	(Desmodesmus	semi-static (Danio rerio)	EC50 = 732 mg/L 30 min	Static (Daphnia magna)
	subspicatus)		_	EC50: = 452 mg/L, 48h
				(Daphnia magna)
				EC50: = 16 mg/L, 21d
				(Daphnia magna)

Persistence and Degradability Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

#### **Mobility**

Will likely be mobile in the environment due to its volatility.

Component	log Pow
1-Chlorobutane	2.66

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

# 14. Transport information

DOT

UN-No UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3 Packing Group II

<u>TDG</u>

**UN-No** UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3 Packing Group II

<u>IATA</u>

UN-No UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1127

Proper Shipping Name CHLOROBUTANES

Hazard Class 3
Packing Group ||

## 15. Regulatory information

### **United States of America Inventory**

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
1-Chlorobutane	109-69-3	X	ACTIVE	-

#### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
1-Chlorobutane	109-69-3	Χ	-	203-696-6	Χ	Χ	Х	Х	Х	KE-05561

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

### U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** - Occupational Safety and

Health Administration

Not applicable

CERCLA Not applicable

California Proposition 65 This product does not contain any Proposition 65 chemicals.

# U.S. State Right-to-Know

Regulations

Component Massachusetts		New Jersey Pennsylvania		Illinois	Rhode Island
1-Chlorobutane	Х	Х	X	-	=

### **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

**Other International Regulations** 

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
1-Chlorobutane	109-69-3	Listed	Not applicable	Not applicable	Not applicable
Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)

1	Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive	Rotterdam Convention (PIC)	Basel Convention
١			(	(2012/18/EC) -		(Hazardous Waste)
١			Qualifying Quantities	, ,		
1			for Major Accident	for Safety Report		
			Notification	Requirements		
	1-Chlorobutane	109-69-3	Not applicable	Not applicable	Not applicable	Annex I - Y45

# 16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 25-May-2009

 Revision Date
 26-Dec-2021

 Print Date
 26-Dec-2021

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**