

SAFETY DATA SHEET

Creation Date 25-May-2009

Revision Date 19-Dec-2025

Revision Number 7

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard 2024 (29 CFR 1910.1200)

1. Identification

Product Name 1-Chlorobutane

Cat No. : AC425880000; AC425880010; AC425880025

CAS No 109-69-3
Synonyms n-Butyl chloride

Recommended Use Research and development.
Uses advised against All other uses.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous according to [US] OSHA (29 CFR 1910.1200, 2024)

| | |
|---------------------|------------|
| Flammable liquids | Category 2 |
| Aspiration Toxicity | Category 1 |

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
May be fatal if swallowed and enters airways

**Precautionary Statements****Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground and bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Wear protective gloves/protective clothing/eye protection/face protection

Take action to prevent static discharges

Use non-sparking tools

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam to extinguish

Storage

Store locked up

Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available

3. Composition/information on Ingredients

| Component | CAS No | Weight % |
|----------------|----------|----------|
| 1-Chlorobutane | 109-69-3 | <=100 |

4. First-aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).

Ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

| | |
|--|--|
| Most important symptoms and effects | Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting |
| Notes to Physician | Treat symptomatically |

5. Fire-fighting measures

| | |
|---|---|
| Suitable Extinguishing Media | Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers. |
| Unsuitable Extinguishing Media | No information available |
| Flash Point | -12 °C / 10.4 °F |
| Method - | No information available |
| Autoignition Temperature | 245 °C / 473 °F |
| Explosion Limits | |
| Upper | 10.1 vol % |
| Lower | 1.0 vol % |
| Sensitivity to Mechanical Impact | No information available |
| Sensitivity to Static Discharge | No information available |

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen chloride gas.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

| Health | Flammability | Instability | Physical hazards |
|--------|--------------|-------------|------------------|
| 3 | 3 | 0 | N/A |

6. Accidental release measures

| | |
|---|---|
| Personal Precautions | Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. |
| Environmental Precautions | Should not be released into the environment. Do not flush into surface water or sanitary sewer system. |
| Methods for Containment and Clean Up | Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. |

7. Handling and Storage

| | |
|-----------------|---|
| Handling | Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges. |
| Storage. | Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents. Strong bases. |

8. Exposure controls / personal protection

| | |
|---|---|
| <u>Exposure Guidelines</u> | This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies. |
| Engineering Measures | Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. |
| <u>Personal Protective Equipment</u> | |
| Eye/face Protection | Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. |
| Skin and body protection | Wear appropriate protective gloves and clothing to prevent skin exposure. |
| Respiratory Protection | Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. |
| Recommended Filter type: | Organic gases and vapours filter. Type A. Brown. conforming to EN14387. |
| Hygiene Measures | Handle in accordance with good industrial hygiene and safety practice. |

9. Physical and chemical properties

| | | |
|--|---|--|
| <u>Appearance</u> | | |
| Physical State | Liquid | |
| Color | Colorless | |
| Odor | No information available | |
| Odor Threshold | No information available | |
| <u>Property</u> | <u>Values</u> | <u>Remarks</u> • <u>Method</u> |
| Melting Point/Range | -123 °C / -189.4 °F | |
| Softening Point | No data available | |
| Boiling Point/Range | 77 - 78 °C / 170.6 - 172.4 °F | @ 760 mmHg |
| Flash Point | -12 °C / 10.4 °F | Method - No information available |
| Flammability (liquid) | Highly flammable | On basis of test data |
| Flammability (solid,gas) | Not applicable | Liquid |
| Explosion Limits | Lower 1 Vol% Upper 10.1 Vol% | |
| Autoignition Temperature | 245 °C / 473 °F | |
| Decomposition Temperature | No data available | |
| pH | No information available | |
| Viscosity | 0.45 mPa.s (20°C) | |
| Water Solubility | Moderately soluble | |
| Solubility in other solvents | No information available | |
| Partition Coefficient (n-octanol/water) | | |
| Component | log Pow | |
| 1-Chlorobutane | 2.66 | |
| Vapor Pressure | 108 mbar @ 20 °C | |
| Density / Specific Gravity | 0.880 | |
| Bulk Density | Not applicable | Liquid |
| Vapor Density | 3.19 (Air = 1.0) | (Air = 1.0) |
| Particle characteristics | Not applicable (liquid) | |

Other Information

| | |
|-----------------------------|---|
| Molecular Formula | C4 H9 Cl |
| Molecular Weight | 92.57 |
| Explosive Properties | Vapors may form explosive mixtures with air |
| Evaporation Rate | No information available |

10. Stability and reactivity

| | |
|---|---|
| Reactive Hazard | None known, based on information available |
| Stability | No information available. |
| Conditions to Avoid | Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. |
| Incompatible Materials | Strong oxidizing agents, Strong bases |
| Hazardous Decomposition Products | Carbon monoxide (CO), Carbon dioxide (CO ₂), Hydrogen chloride gas |
| Hazardous Polymerization | Hazardous polymerization does not occur. |
| Hazardous Reactions | None under normal processing. |

11. Toxicological information

Information on expected route of exposure

| | |
|-------------------|---|
| Inhalation | May cause irritation of respiratory tract. May be harmful if inhaled. |
| Ingestion | May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful if swallowed. Potential for aspiration if swallowed. |
| Eyes | May cause irritation. |
| Skin | May cause irritation. May be harmful in contact with skin. |

Toxicology data for the components

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|----------------|---------------------------|-------------------------------|------------------------------|
| 1-Chlorobutane | LD50 = 2670 mg/kg (Rat) | LD50 > 20000 mg/kg (Rabbit) | LC50 > 7.74 mg/L (Rat) 4 h |

| | |
|---|---|
| Toxicologically Synergistic Products | No information available |
| (b) skin corrosion/irritation; | No data available |
| (c) serious eye damage/irritation; | No data available |
| (d) respiratory or skin sensitization; | |
| Respiratory | No data available |
| Skin | No data available |
| (e) germ cell mutagenicity; | No data available |
| | Mutagenic effects have occurred in experimental animals |
| (f) carcinogenicity; | |

The table below indicates whether each agency has listed any ingredient as a carcinogen

| Component | CAS No | IARC | NTP | ACGIH | OSHA | Mexico |
|-----------|--------|------|-----|-------|------|--------|
|-----------|--------|------|-----|-------|------|--------|

| | | | | | | |
|----------------|----------|------------|------------|------------|------------|------------|
| 1-Chlorobutane | 109-69-3 | Not listed | Not listed | Not listed | Not listed | Not listed |
|----------------|----------|------------|------------|------------|------------|------------|

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; Category 1

Other Adverse Effects Tumorigenic effects have been reported in experimental animals.

Symptoms / effects,both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Other Adverse Effects Tumorigenic effects have been reported in experimental animals.

Endocrine Disrupting Properties This product does not contain any known or suspected endocrine disruptors.

12. Ecological information

Ecotoxicity

Do not empty into drains. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

| Component | Freshwater Algae | Freshwater Fish | Microtox | Water Flea |
|----------------|--|---|---|---|
| 1-Chlorobutane | EC50: > 450 mg/L, 72h (Desmodesmus subspicatus) | LC50: = 71.4 mg/L, 96h semi-static (Danio rerio) | EC50 = 485 mg/L 5 min EC50 = 732 mg/L 30 min | EC50: = 3020 mg/L, 48h Static (Daphnia magna) EC50: = 452 mg/L, 48h (Daphnia magna) EC50: = 16 mg/L, 21d (Daphnia magna) |

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

| Component | log Pow |
|----------------|---------|
| 1-Chlorobutane | 2.66 |

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1127
Proper Shipping Name CHLOROBUTANES
Hazard Class 3
Packing Group II

TDG

UN-No UN1127
Proper Shipping Name CHLOROBUTANES
Hazard Class 3
Packing Group II

IATA

UN-No UN1127
Proper Shipping Name CHLOROBUTANES
Hazard Class 3
Packing Group II

IMDG/IMO

UN-No UN1127
Proper Shipping Name CHLOROBUTANES
Hazard Class 3
Packing Group II

15. Regulatory Information

United States of America Inventory

| Component | CAS No | TSCA | TSCA Inventory notification - Active-Inactive | TSCA - EPA Regulatory Flags |
|----------------|----------|------|--|--------------------------------|
| 1-Chlorobutane | 109-69-3 | X | ACTIVE | - |

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT) Not applicable

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

| Component | CAS No | DSL | NDSL | EINECS | PICCS | ENCS | ISHL | AICS | IECSC | KECL |
|----------------|----------|-----|------|-----------|-------|------|------|------|-------|----------|
| 1-Chlorobutane | 109-69-3 | X | - | 203-696-6 | X | X | X | X | X | KE-05561 |

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

| Component | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|----------------|---------------|------------|--------------|----------|--------------|
| 1-Chlorobutane | X | X | X | - | - |

U.S. Department of Transportation

Reportable Quantity (RQ): N
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations**Mexico - Grade**

Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

Not applicable

| Component | CAS No | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|----------------|----------|---|---|---|
| 1-Chlorobutane | 109-69-3 | - | - | - |

Safety, health and environmental regulations/legislation specific for the substance or mixture

| Component | CAS No | OECD HPV | Persistent Organic Pollutant | Ozone Depletion Potential | Restriction of Hazardous Substances (RoHS) |
|----------------|----------|----------|------------------------------|---------------------------|--|
| 1-Chlorobutane | 109-69-3 | Listed | Not applicable | Not applicable | Not applicable |

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Other International Regulations

| Component | CAS No | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements | Rotterdam Convention (PIC) | Basel Convention (Hazardous Waste) |
|----------------|----------|---|--|----------------------------|------------------------------------|
| 1-Chlorobutane | 109-69-3 | Not applicable | Not applicable | Not applicable | Annex I - Y45 |

16. Other Information

Prepared By Product stewardship (Regulatory Affairs)
Thermo Fisher Scientific
email - begel.sdsdesk@thermofisher.com

Creation Date 25-May-2009
Revision Date 19-Dec-2025
Print Date 19-Dec-2025
Revision Summary Updated to the U.S. Department of Labor's Occupational Safety and Health Administration (OSHA) which published its Final Rule in the Federal Register revising the Hazard Communication Standard (HCS/HazCom), 29 CFR 1910.1200 (2024) (HCS §1910.1200, 2024), May 20, 2024, effective July 19, 2024.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS