

SAFETY DATA SHEET

Creation Date 19-Jun-2009

Revision Date 19-Dec-2025

Revision Number 9

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard 2024 (29 CFR 1910.1200)

1. Identification

Product Name Ammonia, ca 7N solution in methanol

Cat No. : AC428380000; AC428380010; AC428381000; AC428388000

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous according to [US] OSHA (29 CFR 1910.1200, 2024)

Flammable liquids	Category 2
Acute oral toxicity	Category 3
Acute dermal toxicity	Category 3
Acute Inhalation Toxicity - Vapors	Category 3
Skin Corrosion/Irritation	Category 1 B
Serious Eye Damage/Eye Irritation	Category 1
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Optic nerve, Central nervous system (CNS).	

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
Causes severe skin burns and eye damage
Causes damage to organs
Toxic if swallowed, in contact with skin or if inhaled

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Wear protective gloves/protective clothing/eye protection/face protection
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground and bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Keep cool
Wear respiratory protection
Take action to prevent static discharges
Use non-sparking tools

Response

Immediately call a POISON CENTER or doctor

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing
Immediately call a POISON CENTER or doctor

Skin

Take off contaminated clothing and wash before reuse
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Ingestion

Rinse mouth
Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam to extinguish

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

Corrosive to the respiratory tract

Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS.
WARNING. Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/information on Ingredients

Component	CAS No	Weight %
Methyl alcohol	67-56-1	88
Ammonia	7664-41-7	12

4. First-aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Inhalation	If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Most important symptoms and effects	Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Water may be ineffective
Flash Point	14 °C / 57.2 °F
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Nitrogen oxides (NOx). Ammonia. Formaldehyde.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health 3	Flammability 3	Instability 1	Physical hazards N/A
--------------------	--------------------------	-------------------------	--------------------------------

6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and Storage

Handling Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage. Store under an inert atmosphere. Refrigerator/flammables. Keep container tightly closed. Air sensitive. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents. Acids. Acid chlorides. Acid anhydrides. Strong reducing agents. Water. Halogens.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m ³ Skin TWA: 200 ppm TWA: 260 mg/m ³	IDLH: 6000 ppm REL = 200 ppm (TWA) REL = 260 mg/m ³ (TWA) STEL: 250 ppm STEL: 325 mg/m ³	TWA: 200 ppm STEL: 250 ppm
Ammonia	TWA: 25 ppm STEL: 35 ppm	(Vacated) STEL: 35 ppm (Vacated) STEL: 27 mg/m ³ TWA: 50 ppm TWA: 35 mg/m ³	IDLH: 300 ppm REL = 25 ppm (TWA) REL = 18 mg/m ³ (TWA) STEL: 35 ppm STEL: 27 mg/m ³	TWA: 25 ppm STEL: 35 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Tight sealing safety goggles. Face protection shield.
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure.
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended Filter type:	Particulates filter conforming to EN 143. or. Inorganic gases and vapours filter. Type B. Grey. conforming to EN14387.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance			
Physical State	Liquid		
Color	Clear Colorless - Light yellow		
Odor	Ammonia-like		
Odor Threshold	No information available		
Property	Values	Remarks	Method
Melting Point/Range	No data available		
Softening Point	No data available		
Boiling Point/Range	No information available		
Flash Point	14 °C / 57.2 °F		Method - No information available
Flammability (liquid)	Highly flammable		On basis of test data
Flammability (solid,gas)	Not applicable		Liquid
Explosion Limits	No data available		
Autoignition Temperature	No data available		
Decomposition Temperature	No data available		
pH	Not applicable		
Viscosity	No data available		
Water Solubility	No information available		
Solubility in other solvents	No information available		
Partition Coefficient (n-octanol/water)			
Component	log Pow		
Methyl alcohol	-0.74		
Vapor Pressure	No data available		
Density / Specific Gravity	0.770		
Bulk Density	Not applicable	Liquid	
Vapor Density	No data available	(Air = 1.0)	
Particle characteristics	Not applicable (liquid)		
Other Information			
Explosive Properties	Vapors may form explosive mixtures with air		

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Hygroscopic.
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to moist air or water.

Incompatible Materials Strong oxidizing agents, Acids, Acid chlorides, Acid anhydrides, Strong reducing agents, Water, Halogens

Hazardous Decomposition Products Nitrogen oxides (NOx), Ammonia, Formaldehyde

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Information on expected route of exposure

Inhalation Causes burns. Toxic by inhalation. INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS. Harmful by inhalation.

Ingestion Causes burns. Aspiration hazard. Toxic if swallowed. May cause central nervous system effects. Ingestion causes burns of the upper digestive and respiratory tracts. Can burn mouth, throat, and stomach. Harmful if swallowed.

Eyes Causes burns. Corrosive to the eyes and may cause severe damage including blindness. Risk of serious damage to eyes.

Skin Causes burns. Toxic in contact with skin.

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Ammonia	LD50 = 350 mg/kg (Rat)	-	LC50 = 9850 mg/m ³ (Rat) 1 h LC50 = 13770 mg/m ³ (Rat) 1 h

Toxicologically Synergistic Products No information available

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;
Respiratory No data available
Skin No data available

Component	Test method	Test species	Study result
Methyl alcohol 67-56-1 (88)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity; No data available

(f) carcinogenicity;

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed
Ammonia	7664-41-7	Not listed	Not listed	Not listed	Not listed	Not listed

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Methyl alcohol 67-56-1 (88)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

(h) STOT-single exposure; Category 1

Results / Target organs Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs Optic nerve, Skin, Respiratory system, Eyes, Gastrointestinal tract (GI), Blood, Kidney, Liver, Central nervous system (CNS), Heart, spleen.

(j) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

Other Adverse Effects The toxicological properties have not been fully investigated.

Endocrine Disrupting Properties This product does not contain any known or suspected endocrine disruptors.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is: Very toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h
Ammonia	Not listed	LC50: 0.26 - 4.6 mg/L, 96h (Lepomis macrochirus) LC50: = 1.17 mg/L, 96h flow-through (Lepomis macrochirus) LC50: 0.73 - 2.35 mg/L, 96h (Pimephales promelas) LC50: = 5.9 mg/L, 96h static (Pimephales promelas) LC50: > 1.5 mg/L, 96h (Poecilia reticulata) LC50: = 1.19 mg/L, 96h static (Poecilia reticulata) LC50: = 0.44 mg/L, 96h (Cyprinus carpio)	EC50 = 2.0 mg/L 5 min	EC50 = 25.4 mg/L, 48h (Daphnia magna) NOEC = 0.79 mg/L (Daphnia magna)

Persistence and Degradability Persistence is unlikely

Bioaccumulation/ Accumulation No information available.

Mobility .

Component	log Pow
-----------	---------

Methyl alcohol	-0.74
----------------	-------

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

14. Transport information

DOT

UN-No UN3286
Proper Shipping Name Flammable liquid, toxic, corrosive, n.o.s.
Technical Shipping Name Methanol, ammonia
Hazard Class 3
Subsidiary Hazard Class 6.1, 8
Packing Group II

TDG

UN-No UN3286
Proper Shipping Name Flammable liquid, toxic, corrosive, n.o.s.
Technical Shipping Name Methanol, ammonia
Hazard Class 3
Subsidiary Hazard Class 6.1, 8
Packing Group II

IATA

UN-No UN3286
Proper Shipping Name FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S.*
Technical Shipping Name Methanol, ammonia
Hazard Class 3
Subsidiary Hazard Class 6.1, 8
Packing Group II

IMDG/IMO

UN-No UN3286
Proper Shipping Name Flammable liquid, toxic, corrosive, n.o.s.
Technical Shipping Name Methanol, ammonia
Hazard Class 3
Subsidiary Hazard Class 6.1, 8
Packing Group II

15. Regulatory Information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Methyl alcohol	67-56-1	X	ACTIVE	-
Ammonia	7664-41-7	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Methyl alcohol	67-56-1	X	-	200-659-6	X	X	X	X	X	KE-23193
Ammonia	7664-41-7	X	-	231-635-3	X	X	X	X	X	KE-01625

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting thresholds
Methyl alcohol	67-56-1	88	1.0 %	-
Ammonia	7664-41-7	12	1.0 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Ammonia	X	100 lb	-	-

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

OSHA - Occupational Safety and Health Administration

Component	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Ammonia	-	TQ: 10000 lb TQ: 15000 lb

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Methyl alcohol	5000 lb	-	5000 lb 2270 kg
Ammonia	100 lb	100 lb	100 lb 45.4 kg

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Methyl alcohol	67-56-1	Developmental	-	Developmental

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl alcohol	X	X	X	X	X
Ammonia	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
 DOT Marine Pollutant Y
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product contains the following DHS chemicals:

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard
Ammonia	Release STQs - 10000lb (anhydrous) Release STQs - 20000lb (concentration >=20%)

Other International Regulations**Mexico - Grade** No information available**Authorisation/Restrictions according to EU REACH**

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	67-56-1	-	Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Ammonia	7664-41-7	-	Use restricted. See entry 75. (see link for restriction details)	-

REACH links<https://echa.europa.eu/substances-restricted-under-reach>**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable
Ammonia	7664-41-7	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities	Seveso III Directive (2012/18/EC) - Qualifying Quantities	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)

		for Major Accident Notification	for Safety Report Requirements		
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable
Ammonia	7664-41-7	50 tonne	200 tonne	Not applicable	Not applicable

16. Other Information

Prepared By	Product stewardship (Regulatory Affairs) Thermo Fisher Scientific email - begel.sdsdesk@thermofisher.com
Creation Date	19-Jun-2009
Revision Date	19-Dec-2025
Print Date	19-Dec-2025
Revision Summary	Updated to the U.S. Department of Labor's Occupational Safety and Health Administration (OSHA) which published its Final Rule in the Federal Register revising the Hazard Communication Standard (HCS/HazCom), 29 CFR 1910.1200 (2024) (HCS §1910.1200, 2024), May 20, 2024, effective July 19, 2024.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS