

SAFETY DATA SHEET

Creation Date 24-Mar-2014 Revision Date 28-Dec-2021 Revision Number 5

1. Identification

Product Name p-Xylene

Cat No.: AC445680000, AC445680010, AC445680025, AC445681000

CAS No 106-42-3

Synonyms 1,4-Dimethylbenzene

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number For information US call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Acute dermal toxicity

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Target Organs - Central nervous system (CNS), Respiratory system.

Aspiration Toxicity

Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation
Harmful in contact with skin or if inhaled



Precautionary Statements

Prevention

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Indestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Harmful to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS No	Weight %
p-Xylene	106-42-3	>95

Revision Date 28-Dec-2021 p-Xylene

4. First-aid measures

Eve Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. Risk of serious damage to the lungs (by

aspiration).

Ingestion Aspiration hazard. Do NOT induce vomiting. Call a physician or poison control center

immediately. If vomiting occurs naturally, have victim lean forward.

Most important symptoms and

effects

Difficulty in breathing. . Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting Treat symptomatically

Notes to Physician

5. Fire-fighting measures

Suitable Extinguishing Media CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media Water may be ineffective

25 °C / 77 °F **Flash Point**

Method -No information available

465 °C / 869 °F **Autoignition Temperature**

Explosion Limits

Upper 7.0 vol % 1.1 vol % Lower

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2). Hydrocarbons. Aldehydes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health Instability Physical hazards **Flammability** N/A

Accidental release measures

Personal Precautions Use personal protective equipment as required. Remove all sources of ignition. Take

precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

Environmental Precautions

Avoid release to the environment. See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system. Collect spillage.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, **Up** closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Use only under a chemical fume hood. Use spark-proof tools and explosion-proof equipment. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only

non-sparking tools.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing

agents. Strong acids. Strong bases.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
p-Xylene	TWA: 100 ppm		IDLH: 900 ppm	TWA: 100 ppm
	STEL: 150 ppm		TWA: 100 ppm	STEL: 150 ppm
			TWA: 435 mg/m ³	
			STEL: 150 ppm	
			STEL: 655 mg/m ³	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting

equipment. Ensure that eyewash stations and safety showers are close to the workstation

location. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid
Appearance Colorless
Odor aromatic

Odor Threshold No information available

pH Not applicable Melting Point/Range 13 °C / 55.4 °F

Boiling Point/Range138 °C / 280.4 °FFlash Point25 °C / 77 °FEvaporation RateNo information available

Flammability (solid,gas)

Not applicable

Flammability or explosive limits

 Upper
 7.0 vol %

 Lower
 1.1 vol %

 Vapor Pressure
 8 mbar @ 20 °C

 Vapor Density
 3.7 (Air = 1.0)

Specific Gravity 0.866

SolubilityNo information availablePartition coefficient; n-octanol/waterNo data availableAutoignition Temperature465 °C / 869 °FDecomposition TemperatureNo information availableViscosity0.648 mPa.s (20°C)

Molecular Formula C8 H10 Molecular Weight 106.17

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Strong bases

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Hydrocarbons, Aldehydes

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
p-Xylene	LD50 = 4029 mg/kg (Rat)	LD50 = 12126 mg/kg (Rabbit)	LC50 = 4740 ppm (Rat) 4 h

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes, respiratory system and skin

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
p-Xylene	106-42-3	Not listed				

Mutagenic Effects No information available

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals.

Developmental EffectsDevelopmental effects have occurred in experimental animals.

Revision Date 28-Dec-2021 p-Xylene

Teratogenicity Teratogenic effects have occurred in experimental animals.

STOT - single exposure Central nervous system (CNS) Respiratory system

STOT - repeated exposure None known

Aspiration hazard Category 1

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

delayed

Endocrine Disruptor Information No information available

Other Adverse Effects See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Do not empty into drains. The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
p-Xylene	EC50: = 3.2 mg/L, 72h static	LC50: = 8.8 mg/L, 96h	EC50 = 5.7 mg/L 30 min	EC50: 3.55 - 6.31 mg/L, 48h
	(Pseudokirchneriella	semi-static (Poecilia	_	Static (Daphnia magna)
	subcapitata)	reticulata)		
		LC50: = 2.6 mg/L, 96h static		
		(Oncorhynchus mykiss)		
		LC50: = 2.6 mg/L, 96h		
		(Oncorhynchus mykiss)		
		LC50: 7.2 - 9.9 mg/L, 96h		
		static (Pimephales		
		promelas)		
		,		

Persistence and Degradability

Insoluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation

No information available.

Mobility

. Is not likely mobile in the environment due its low water solubility. Will likely be mobile in the environment due to its volatility.

Component	log Pow
p-Xylene	3.15

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN1307 **UN-No Proper Shipping Name XYLENES Hazard Class Packing Group** Ш

TDG

UN-No UN1307 **XYLENES Proper Shipping Name Hazard Class Packing Group** Ш

IATA

Revision Date 28-Dec-2021 p-Xylene

UN-No UN1307 **Proper Shipping Name XYLENES**

Hazard Class Packing Group Ш

IMDG/IMO

UN1307 **UN-No Proper Shipping Name XYLENES Hazard Class**

Ш **Packing Group**

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
p-Xylene	106-42-3	Χ	ACTIVE	-

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed '-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

	Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
ı	p-Xylene	106-42-3	Х	-	203-396-5	Χ	Χ	Х	Χ	Χ	KE-35430

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %
p-Xylene	106-42-3	>95	1.0

See section 2 for more information SARA 311/312 Hazard Categories

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
p-Xylene	X	-	-	-

Clean Air Act

CERCLA

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
p-Xylene	X		-

OSHA - Occupational Safety and

Not applicable

Health Administration

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs

p-Xylene	100 lb	-

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

-	Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
	p-Xylene	X	X	X	X	-

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Component

Mexico - Grade Moderate risk, Grade 2

Authorisation/Restrictions according to EU REACH

Component		REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous	
	Authorization	Substances	List of Substances of Very High Concern (SVHC)
p-Xylene	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No

			Pollutant	Potential	Hazardous Substances (RoHS)
p-Xylene	106-42-3	Listed	Not applicable	Not applicable	Not applicable
Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
p-Xylene	106-42-3	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

OECD HPV

 Creation Date
 24-Mar-2014

 Revision Date
 28-Dec-2021

 Print Date
 28-Dec-2021

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Restriction of

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS