

# SAFETY DATA SHEET

Creation Date 29-Jan-2018

Revision Date 18-Dec-2025

Revision Number 3

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard 2024 (29 CFR 1910.1200)

## 1. Identification

**Product Name** Ethanol, denatured

**Cat No. :** AC463690000; AC463690010; AC463690050; AC463690250

**Synonyms** No information available

**Recommended Use** Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

### Details of the supplier of the safety data sheet

#### Company

Fisher Scientific Company  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

Acros Organics  
One Reagent Lane  
Fair Lawn, NJ 07410

#### **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## 2. Hazard(s) identification

### Classification

This chemical is considered hazardous according to [US] OSHA (29 CFR 1910.1200, 2024)

Flammable liquids	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	

### Label Elements

#### **Signal Word**

Danger

#### **Hazard Statements**

Highly flammable liquid and vapor  
Causes serious eye irritation  
May cause drowsiness or dizziness



### Precautionary Statements

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 Keep container tightly closed  
 Ground and bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting equipment  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Take action to prevent static discharges  
 Use non-sparking tools

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention

#### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish

#### Storage

Store in a well-ventilated place. Keep cool

#### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

#### Hazards classified under paragraph (d)(1)(ii) of 1910.1200

No information available

#### Other hazards

Contains a known or suspected endocrine disruptor.

## 3. Composition/information on Ingredients

Component	CAS No	Weight %
Ethyl alcohol	64-17-5	>95
Methyl ethyl ketone	78-93-3	1
Isopropyl alcohol	67-63-0	1
Denatonium benzoate	3734-33-6	0.001

## 4. First-aid measures

#### General Advice

If symptoms persist, call a physician.

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

#### Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

**Ingestion**

Clean mouth with water and drink afterwards plenty of water.

**Most important symptoms and effects**

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

**Notes to Physician**

Treat symptomatically

## 5. Fire-fighting measures

**Suitable Extinguishing Media**

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

**Unsuitable Extinguishing Media**

No information available

**Flash Point**

12 °C / 53.6 °F

**Method -**

No information available

**Autoignition Temperature**

363 °C / 685.4 °F

**Explosion Limits****Upper**

No data available

**Lower**

No data available

**Sensitivity to Mechanical Impact** No information available

**Sensitivity to Static Discharge** No information available

**Specific Hazards Arising from the Chemical**

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

**Hazardous Combustion Products**

None known.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**NFPA**

**Health**  
2

**Flammability**  
3

**Instability**  
0

**Physical hazards**  
N/A

## 6. Accidental release measures

**Personal Precautions**

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions**

Do not flush into surface water or sanitary sewer system.

**Methods for Containment and Clean Up**

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and Storage

**Handling**

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

**Storage.**

Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

## 8. Exposure controls / personal protection

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m <sup>3</sup> TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm REL = 1000 ppm (TWA) REL = 1900 mg/m <sup>3</sup> (TWA)	STEL: 1000 ppm
Methyl ethyl ketone	TWA: 200 ppm STEL: 300 ppm	(Vacated) TWA: 200 ppm (Vacated) TWA: 590 mg/m <sup>3</sup> (Vacated) STEL: 300 ppm (Vacated) STEL: 885 mg/m <sup>3</sup> TWA: 200 ppm TWA: 590 mg/m <sup>3</sup>	IDLH: 3000 ppm REL = 200 ppm (TWA) REL = 590 mg/m <sup>3</sup> (TWA) STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 300 ppm
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m <sup>3</sup> (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m <sup>3</sup> TWA: 400 ppm TWA: 980 mg/m <sup>3</sup>	IDLH: 2000 ppm REL = 400 ppm (TWA) REL = 980 mg/m <sup>3</sup> (TWA) STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 400 ppm

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

### Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

### Personal Protective Equipment

#### Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

#### Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

#### Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

#### Recommended Filter type:

Organic gases and vapours filter. Type A. Brown. conforming to EN14387.

#### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

### Appearance

#### Physical State

Liquid

#### Color

#### Odor

No information available

#### Odor Threshold

No information available

### Property

#### Melting Point/Range

-114.1 °C / -173.4 °F

#### Softening Point

No data available

#### Remarks

#### Method

<b>Boiling Point/Range</b>	78 °C / 172.4 °F	@ 760 mmHg
<b>Flash Point</b>	12 °C / 53.6 °F	<b>Method</b> - No information available
<b>Flammability (liquid)</b>	Highly flammable	On basis of test data
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	<b>Lower</b> 2.5 <b>Upper</b> 13.5	
<b>Autoignition Temperature</b>	363 °C / 685.4 °F	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	5.7	
<b>Viscosity</b>	No data available	
<b>Water Solubility</b>	Soluble	
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
Ethyl alcohol	-0.32	
Methyl ethyl ketone	0.29	
Isopropyl alcohol	0.05	
Denatonium benzoate	2.2	
<b>Vapor Pressure</b>	57 hPa @ 20°C	
<b>Density / Specific Gravity</b>	0.79	
<b>Bulk Density</b>	Not applicable	Liquid
<b>Vapor Density</b>	No data available	(Air = 1.0)
<b>Particle characteristics</b>	Not applicable (liquid)	

**Other Information**

**Explosive Properties** Vapors may form explosive mixtures with air

## 10. Stability and reactivity

<b>Reactive Hazard</b>	None known, based on information available
<b>Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Keep away from open flames, hot surfaces and sources of ignition.
<b>Incompatible Materials</b>	Strong oxidizing agents
<b>Hazardous Decomposition Products</b>	None under normal use conditions
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	None under normal processing.

## 11. Toxicological information

**Information on expected route of exposure**

<b>Inhalation</b>	Avoid breathing vapors or mists.
<b>Ingestion</b>	May be harmful if swallowed.
<b>Eyes</b>	Avoid contact with eyes. Irritating to eyes. Vapor may cause irritation.
<b>Skin</b>	Avoid contact with skin. May cause irritation. Prolonged skin contact may defat the skin and produce dermatitis.

**Toxicology data for the components**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg OECD 401 (Rat) 3450 mg/kg ( Mouse )	-	LC50 = 117-125 mg/l (4h) OECD 403 (rat) 20000 ppm/10H (rat)

Methyl ethyl ketone	LD50 = 2483 mg/kg ( Rat )	LD50 = 5000 mg/kg ( Rabbit )	LC50 = 11700 ppm ( Rat ) 4 h
Isopropyl alcohol	5045 mg/kg ( Rat ) 3600 mg/kg ( Mouse )	12800 mg/kg ( Rat )	72.6 mg/L ( Rat ) 4 h
Denatonium benzoate	LD50 = 584 mg/kg ( Rat )	LD50 > 2000 mg/kg ( Rat )	LC50 = 0.2 mg/L ( Rat ) 4 h

**Toxicologically Synergistic Products** No information available

**(b) skin corrosion/irritation;** Based on available data, the classification criteria are not met

**(c) serious eye damage/irritation;** Category 2

**(d) respiratory or skin sensitization;**

**Respiratory**  
**Skin**

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Ethyl alcohol 64-17-5 ( >95 )	Mouse Ear Swelling Test (MEST)	mouse	non-sensitising
	----- OECD Test Guideline 429 Local Lymph Node Assay	mouse	non-sensitising

**(e) germ cell mutagenicity;** Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Ethyl alcohol 64-17-5 ( >95 )	AMES test OECD Test Guideline 471	in vitro Bacteria	negative
	----- Gene cell mutation OECD Test Guideline 476	in vitro Mammalian	negative

**(f) carcinogenicity;** Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl alcohol	64-17-5	Not listed	Known	A3	Not listed	A3
Methyl ethyl ketone	78-93-3	Not listed				
Isopropyl alcohol	67-63-0	Not listed				
Denatonium benzoate	3734-33-6	Not listed				

*IARC (International Agency for Research on Cancer)*

*NTP: (National Toxicity Program)*

*ACGIH: (American Conference of Governmental Industrial Hygienists)*

*Mexico - Occupational Exposure Limits - Carcinogens*

*IARC (International Agency for Research on Cancer)*

*Group 1 - Carcinogenic to Humans*

*Group 2A - Probably Carcinogenic to Humans*

*Group 2B - Possibly Carcinogenic to Humans*

*NTP: (National Toxicity Program)*

*Known - Known Carcinogen*

*Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen*

*A1 - Known Human Carcinogen*

*A2 - Suspected Human Carcinogen*

*A3 - Animal Carcinogen*

*ACGIH: (American Conference of Governmental Industrial Hygienists)*

*Mexico - Occupational Exposure Limits - Carcinogens*

*A1 - Confirmed Human Carcinogen*

*A2 - Suspected Human Carcinogen*

*A3 - Confirmed Animal Carcinogen*

*A4 - Not Classifiable as a Human Carcinogen*

A5 - Not Suspected as a Human Carcinogen

**(g) reproductive toxicity;**

Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Ethyl alcohol 64-17-5 ( >95 )	OECD Test Guideline 416	Oral / mouse 2 Generation	NOAEL = 13.8 g/kg/day
	OECD Test Guideline 414	Inhalation / Rat	NOAEC = 16000 ppm

**(h) STOT-single exposure;**

Based on available data, the classification criteria are not met

**Results / Target organs**

Central nervous system (CNS).

**(i) STOT-repeated exposure;**

Based on available data, the classification criteria are not met

**Target Organs**

None known.

**(j) aspiration hazard;**

Based on available data, the classification criteria are not met

**Symptoms / effects, both acute and delayed**

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Other Adverse Effects**

The toxicological properties have not been fully investigated.

**Endocrine Disrupting Properties****Assess endocrine disrupting properties for human health**

Contains a substance on the National Authorities Endocrine Disruptor Lists

Component	EU National Authorities Endocrine Disruptor Lists - Health
Methyl ethyl ketone 78-93-3 ( 1 )	List II

## 12. Ecological information

**Ecotoxicity**

Contains a substance which is: Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h
Methyl ethyl ketone	Not listed	Lepomis macrochirus: LC50=3,22 g/L 96 h	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50: = 5091 mg/L, 48h (Daphnia magna) EC50: 4025 - 6440 mg/L, 48h Static (Daphnia magna) EC50: > 520 mg/L, 48h (Daphnia magna)
Isopropyl alcohol	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h

		static (Pimephales promelas) LC50: = 10000000 µg/L, 96h (Daphnia)		
--	--	--	--	--

**Persistence and Degradability** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl alcohol	-0.32
Methyl ethyl ketone	0.29
Isopropyl alcohol	0.05
Denatonium benzoate	2.2

### 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl ethyl ketone - 78-93-3	U159	-

### 14. Transport information

#### DOT

UN-No UN1170  
 Proper Shipping Name ETHANOL  
 Hazard Class 3  
 Packing Group II

#### TDG

UN-No UN1170  
 Proper Shipping Name ETHANOL  
 Hazard Class 3  
 Packing Group II

#### IATA

UN-No UN1170  
 Proper Shipping Name ETHANOL  
 Hazard Class 3  
 Packing Group II

#### IMDG/IMO

UN-No UN1170  
 Proper Shipping Name ETHANOL  
 Hazard Class 3  
 Packing Group II

### 15. Regulatory Information

#### United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Ethyl alcohol	64-17-5	X	ACTIVE	-
Methyl ethyl ketone	78-93-3	X	ACTIVE	-
Isopropyl alcohol	67-63-0	X	ACTIVE	-
Denatonium benzoate	3734-33-6	X	ACTIVE	-

#### **Legend:**

**TSCA** US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'- - Not Listed

**TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)** Not applicable

**TSCA 12(b) - Notices of Export** Not applicable

**International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Ethyl alcohol	64-17-5	X	-	200-578-6	X	X	X	X	X	KE-13217
Methyl ethyl ketone	78-93-3	X	-	201-159-0	X	X	X	X	X	KE-24094
Isopropyl alcohol	67-63-0	X	-	200-661-7	X	X	X	X	X	KE-29363
Denatonium benzoate	3734-33-6	X	-	223-095-2	X	X		X	X	KE-11775

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting thresholds
Isopropyl alcohol	67-63-0	1	1.0 %	-

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)** Not applicable

**Clean Air Act** Not applicable

**OSHA - Occupational Safety and Health Administration** Not applicable

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Methyl ethyl ketone	5000 lb	-	5000 lb 2270 kg

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Development (alcoholic beverages only) Carcinogen	-	Developmental Carcinogen

**U.S. State Right-to-Know Regulations**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl alcohol	X	X	X	X	X
Methyl ethyl ketone	X	X	X	X	X
Isopropyl alcohol	X	X	X	-	X

**U.S. Department of Transportation**

Reportable Quantity (RQ): Y  
 DOT Marine Pollutant N  
 DOT Severe Marine Pollutant N

**U.S. Department of Homeland Security** This product does not contain any DHS chemicals.

**Other International Regulations**

**Mexico - Grade** No information available

**Authorisation/Restrictions according to EU REACH**

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl alcohol	64-17-5	-	-	-
Methyl ethyl ketone	78-93-3	-	Use restricted. See entry 75. (see link for restriction details)	-
Isopropyl alcohol	67-63-0	-	Use restricted. See entry 75. (see link for restriction details)	-
Denatonium benzoate	3734-33-6	-	-	-

**REACH links**

<https://echa.europa.eu/substances-restricted-under-reach>

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl alcohol	64-17-5	Listed	Not applicable	Not applicable	Not applicable
Methyl ethyl ketone	78-93-3	Listed	Not applicable	Not applicable	Not applicable
Isopropyl alcohol	67-63-0	Listed	Not applicable	Not applicable	Not applicable
Denatonium benzoate	3734-33-6	Not applicable	Not applicable	Not applicable	Not applicable

**Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?**

Not applicable

**Other International Regulations**

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)

---

Ethyl alcohol	64-17-5	Not applicable	Not applicable	Not applicable	Annex I - Y42
Methyl ethyl ketone	78-93-3	Not applicable	Not applicable	Not applicable	Annex I - Y42
Isopropyl alcohol	67-63-0	Not applicable	Not applicable	Not applicable	Annex I - Y42
Denatonium benzoate	3734-33-6	Not applicable	Not applicable	Not applicable	Not applicable

## 16. Other Information

<b>Prepared By</b>	Product stewardship (Regulatory Affairs) Thermo Fisher Scientific email - begel.sdsdesk@thermofisher.com
<b>Creation Date</b>	29-Jan-2018
<b>Revision Date</b>	18-Dec-2025
<b>Print Date</b>	18-Dec-2025
<b>Revision Summary</b>	Updated to the U.S. Department of Labor's Occupational Safety and Health Administration (OSHA) which published its Final Rule in the Federal Register revising the Hazard Communication Standard (HCS/HazCom), 29 CFR 1910.1200 (2024) (HCS §1910.1200, 2024), May 20, 2024, effective July 19, 2024.

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**